



**Product Name: ARISTA**  
Water-based Decorative finish with Crystal Effect  
Product Code: 101

## DESCRIPTION

ARISTA is a new modern decorative coating for interiors. It has the prismatic effect that changes tone according to the angle from which it is seen, giving a sleek glow to the wall surface.

## SPECIFICATION

- ✓ ARISTA creates different effects under light or shadow.
- ✓ The product has a low odour level, is non flammable and is friendly both to humans and the environment.
- ✓ ARISTA is highly washable
- ✓ ARISTA can be applied to all kinds of plaster surfaces, as well as wood panels, as long as they are treated with appropriate primers.

## APPLICATION INSTRUCTIONS

Ensure that the surface is clean, dry and free from peeling paint or any substance that may compromise adhesion.

Prime the surface using the specific decorative primer Sandeco Decoprimer.

Using a varnish brush, apply two coats of Sandeco Decoprimer with %10-%20 of water and let them dry for 4 hours before applying ARISTA

Over the dry and previously painted surface, apply ARISTA by brush or lambskin roller then using a rag stippler, immediately dab the wet product randomly

Verify spread rates and surface area to be coated to avoid running short of product during the working process and reducing the risk of differences in tones.

Make sure that both the ambient temperature and the substrate temperature are between +5°C and +35°C



**Product Name : ARISTA**

Water-based Decorative finish with Crystal Effect

Product Code: 101

## TECHNICAL FEATURES & PHYSICAL CONSTANTS

<b>COLOURS</b>	Available in a range of SANDECO special color card which can be further increased with special colors
<b>DENSITY</b>	1,06 ± 0,02 gr/cm <sup>3</sup>
<b>VISCOSITY</b>	102- 108 KU
<b>PH</b>	8 - 9
<b>VOLUME SOLIDS, %</b>	43 ± 2
<b>GLOSS GRADE</b>	Matt
<b>FLASH POINT</b>	Non-flammable.
<b>THINNING</b>	Water
<b>DRYING TIME</b>	Dry-to-touch, 2 - 4 hours / In depth,24 Hours (recorded at 23°C)
<b>CONSUMPTION</b>	Depending on porosity of surface and environmental conditions 0.090 – 0.140 L /m <sup>2</sup>
<b>TEMPERATURE FOR APPLICATION</b>	+ 5 °C - + 35 °C
<b>APPLICATION TOOLS</b>	Varnish Brush
<b>SIZES &amp; PACKAGING</b>	1Lt - 2,5Lt - 7,5 Lt
<b>STORAGE AND SHELF LIFE</b>	1 year, unopened in cool frost-free conditions
<b>WARNING</b>	Keep out of the reach of children. Avoid contact with skin and eyes