



## **BASCO AUTOGUARD CELLULOSE PRIMER SURFACER BAN 2**

**Product Description:** Basco Autoguard Cellulose Primer Surfacer is an automotive primer for Auto-finishes on motorcars, trucks, tractors, etc. It is based on a combination of Nitrocellulose and hard quality alkyd resins. Pigments include fillers and high quality inorganic materials that all combine to give a hard fast drying primer.

**Finish:** Matt

**Application:** By spraying only, at a pressure of 40-55 p.s.i.

**Thinning:** Basco Standard Thinner, best mixed at a volume ratio of 1:1 with Cellulose Primer Surfacer

**Dry Time:** Touch dry 5-10 mins in fair weather, overcoatable 30-60 mins

**Cleaning:** Clean equipment with Basco Standard Thinner immediately.

**Colour Range:** Grey, or as required.

**Overcoats:** Basco Autoguard Cellulose, Fast Dry or Two Pack Acrylic finishes.

**Pack Sizes:** ½ litre, 1 litre, 4 litres.

### **SPECIFICATIONS**

- Surface to be primed must be clean, dry, free from dust, oil, grease or any contaminant.
- Sanding down is best when abrasive paper is introduced onto water wet primed surface.
- Filling or smoothing primed surface can be done using Basco Spot Putty on dry Primer.
- Due to its fast air drying formulation the lid must be tightly replaced on unused primer in can.
- Keep way from naked flame. **INFLAMMABLE.**
- Avoid contact with skin or eyes by wearing goggles and protective clothing.
- Spray in well ventilated areas only.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: [customerservice@bascopaints.com](mailto:customerservice@bascopaints.com)

Facebook: BascoProductsKenya

[www.bascopaints.com](http://www.bascopaints.com)

Twitter: @bascopaints