

Basco Autoguard Two Pack Acrylic Primer Surfacer BAA 2

Product Description: Basco Autoguard Two Pack Acrylic Primer Surfacer is a two component Acrylic/ Isocyanate system that provides a safe base for the motorcar finish in this range. It is chemical resistant, flexible and can be rubbed down with abrasive paper conveniently to allow for good adhesion and high gloss of the finish.

Finish: Matt

Application: By spray (or brush if on wood.) Recommended spraying pressure @ 45-55 p.s.i

Thinning: Use Basco Two Pack Acrylic Thinner only. Thinning for spraying is usually added at a ratio of 4:1:1 (paint: hardener: thinner.) Thinner ratio may be exceeded to suit spraying viscosity of 26-28 seconds B4 cup.

Drying Time: Touch dry in 1 hour

Cleaning: Clean equipment with Basco Two Pack Acrylic Thinner

Colour: Grey or as required.

Overcoats: Basco Autoguard Two Pack Acrylic Finishes. Can also serve for Basco Autoguard Cellulose Finishes.

Pack Sizes: ½ litre, 1 litre, 4 litres.

SPECIFICATIONS

- Surface to be primed must be clean, dry, free from dust, oil, grease or any contaminant.
- Mix Primer, Hardener and Thinner at ratio of 4:1:1. Let stand for 30 minutes before spraying.
- Handle primed surface after 24 hours.
- Filling or smoothing use Basco Spot Putty.
- Sanding down is best when abrasive paper is introduced onto water wet primed surface.
- Keep away from naked flame. **INFLAMMABLE**
- Avoid contact with skin and eyes by wearing goggles and protective clothes.
- Spray in well ventilated area only.