

Basco Sanding Sealer BSC 2

Product Description: Basco Sanding Sealer is a high quality wood furniture product used especially where a very high degree of gloss is desired on the lacquer topcoats. It is formulated to allow sanding with ease using fine adhesive paper.

Finish: Matt

Application: By Spray. Thin to sprayable viscosity i.e. 25sec B4 cup @ 25°C. Can be applied by brush also.

Thinning: Use Basco Standard Thinner.

Drying Time: Touch dry 5 -10 minutes. Recoatable (By spray only) 10 minutes. Overcoatable after 12 hours.

Cleaning: Clean all equipment with Basco Standard Thinner.

Colour: Clear

Spread Rate: 10-12 sq. mts per litre. May extend if sprayed

Pack Sizes: ½ litre, 1 litre, 4 litres, 20 litres

SPECIFICATIONS

Surface Preparation:

- 1) Sand down the wooden surface lightly.
- 2) Dust off thoroughly using solvent-wet rag to ensure dust free surface.

New or old wood surfaces:

- 1) If brush application, apply only one coat liberally. If spray application, apply at least 3 coats wet on wet allowing 10 minutes between coats.
- 2) Dry sanding may commence after 12 hours. Ensure final abrasion paper grade is the fine grid.
- 3) Leave overnight for full cure, dust off.
- 4) Apply the desired Wood Finish N.C. lacquer, or any other desired lacquer.

CAUTION

1. Highly **INFLAMMABLE**. Keep away from naked flames.
2. Wear eye protection, breathing mask and hand gloves while handling Basco Sanding Sealer.