



DURACOAT ACRYLIC SEALER DDC 1

Product Description: Duracoat Acrylic Sealer is based on styrene acrylic, a resin which gives outstanding sealing properties. It is also designed to give a protective transparent coating on monumental stone, coral stone or cement-based stone whose natural appearance is desired. Not suitable for floors or high friction areas.

Finish: Matt

Application: By brush, roller, spray

Thinning: Supplied ready for use

Drying Time: Surface dry: 10 minutes. Recoating time: 1 hour.

Cleaning: Clean all equipment immediately with water

Colour Range: Whitish, but dries to a clear matt finish

Spread Rate: 14-16 sq. mts. per litre when properly applied on smooth surfaces. Spreading rate will vary on rough surfaces and degree of porosity.

Pack Sizes: 1 litre, 4 litres, 20 litres

SPECIFICATIONS:

On exceptionally porous surface apply one coat of Duracoat Acrylic Sealer. Make sure the surface is dust free before application. Allow overnight drying before applying a second coat of the same.

Duracoat Acrylic Sealer may be over coated with water based acrylics such as Duracoat Emulsions.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: customerservice@bascopaints.com

Facebook: BascoProductsKenya

www.bascopaints.com

Twitter: @bascopaints