



DURACOAT ALUMINIUM WOOD PRIMER DDP 3

Product Description: A high quality primer designed for new and bare wood work on both hard and soft wood. It is hard drying with good penetration and excellent adhesion, is easy to apply. Also recommended for cases where the finish colour is being changed.

Finish: Matt

Application: By brush, spray

Thinning: Supplied ready for use but may be thinned to ease brushing or spray application using Duracoat White Spirit

Drying time: Surface dry 2-4 hours. Overcoatable 12 hours.

Cleaning: Clean all equipment with Duracoat White Spirit

Colour Range: Metallic Grey

Spread Rate: 11-14 sq. mts per litre when applied by brush on smooth surfaces. This will vary when sprayed.

Pack Sizes: 1 litre, 4 litres, 20 litres

SPECIFICATIONS:

New Wood Surface: Make sure that the wood is dry. Apply one coat Duracoat Aluminium Wood Primer before applying the desired finish, allowing at least 14 hours between coats in fair weather.

Previously Painted Wood Surfaces: Remove all flaking paint, sand down then apply one coat of Duracoat Aluminium Wood Primer before applying the finish coat.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: customerservice@bascopaints.com

Facebook: BascoProductsKenya

www.bascopaints.com

Twitter: @bascopaints