



DURACOAT BITUMINOUS ALUMINIUM PAINT DSI 2

Product Description: Duracoat Bituminous Aluminium Paint is a high quality paint based on bituminous solution and aluminium flakes. It is recommended as a heat reflecting finishing coat on metal pipes, corrugated iron and flat roofs, metal tanks and bitumen felt. It is durable and flexible and has good adhesion to most surfaces.

Finish: Dull Metallic

Application: By brush or spray

Thinning: Supplied ready for brush application. Thin with Duracoat White Spirit for spray application.

Drying time: Surface dry: 1-2 hours. Recoating: 12 hours

Cleaning: Clean all equipment with Duracoat White Spirit

Colour: Metallic Grey

Spread Rate: 14-16sq. mts per litre when applied on smooth surface. Spread rate will vary if applied on rough surfaces

Pack Sizes: 1 litre, 4 litres, 20 litres

SPECIFICATIONS:

Apply Duracoat Bituminous Aluminium Paint direct on to the surface. No priming is necessary on felt. If on metal ensure it is appropriately primed. One coat is sufficient, but two coats are recommended for maximum durability. Allow 12 hours between coats.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: customerservice@bascopaints.com

Facebook: BascoProductsKenya

www.bascopaints.com

Twitter: @bascopaints