



Duracoat Eggshell Finish DDG 3

Product Description:

A semi-matt oil-based finish for use on walls, wooden surfaces and high traffic areas. It is made from high quality oil-modified alkyd resins and selected light-fast pigments.

Finish:

Semi-matt (like the shell of an egg)

Application:

By brush, roller or spray

Thinning:

Thin with Duracoat White Spirit. Stir well on opening.

Drying time:

Dust free 2-4 hours. Recoatable in 16 hours

Cleaning:

Clean equipment with Duracoat White Spirit

Colour Range:

Available in a wide range of colours from Duracoat Colour Card, Duracoat Classic and Colour Plus fandecks.

Spread Rate:

12-15 sq.m/litre depending on surface texture and porosity

Pack Sizes:

1 litre, 4 litres, and 20 litres

Specifications:

New Wood Surfaces:

Surface must be clean and dry. Apply one coat of Duracoat White or Aluminium Wood Primer followed by one coat of Duracoat Universal Undercoat. Follow up with two coats of Duracoat Eggshell Finish, allowing 16 hours drying time between coats.

Metal Surfaces:

Apply one coat of Duracoat Red Oxide Zinc Chromate Primer to ferrous substrate and Duracoat Zinc Chromate Primer to non-ferrous surfaces followed by one coat of Duracoat Universal Undercoat. Follow up with two coats of Duracoat Eggshell Finish, allowing 16 hours drying time between coats.

Plaster and Cement Surfaces:

The surface to be painted must be dry; ensure there is no moisture on the surface. Apply one coat of Duracoat Emulsion Undercoat before applying two coats of Duracoat Eggshell Finish, allowing 16 hours drying time between coats.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: customerservice@bascopaints.com

Facebook: BascoProductsKenya

www.bascopaints.com

Twitter: @bascopaints