



DURACOAT EMULSION UNDERCOAT DDU 1

Product Description: A premium quality smooth flowing primer that provides excellent abrasion and sealing characteristics for interior surfaces. Ideally suitable for soft boards, gypsum, hardboard and cement plaster.

Finish: Matt

Application: By brush, roller or spray.

Thinning: Supplied ready for use but can be thinned to brushable viscosity using clean water.

Drying time: Dust free 2-4 hours

Cleaning: Clean equipment with water

Colour Range: White and Light colours.

Spread Rate: 11-14 sq. mts. per litre, depending on texture of surface.

Pack Sizes: 1 litre, 4 litres, 20 litres

SPECIFICATIONS:

New surfaces: Surface must be clean, dry and free from grease. Apply one coat of Duracoat Emulsion Undercoat followed by two coats of Duracoat Matt Emulsion, or desired finish allowing over 4 hrs drying after the Undercoat.

Previously painted surfaces: Remove all old flaking paint from the surface and rub down the surface. Apply one coat of Duracoat Emulsion Undercoat followed by two coats of Duracoat Vinyl Matt or desired finish, allowing over 4hrs drying after the Undercoat.

Metal Surfaces: Not recommended.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: customerservice@bascopaints.com

Facebook: [BascoProductsKenya](https://www.facebook.com/BascoProductsKenya)

www.bascopaints.com

Twitter: [@bascopaints](https://twitter.com/bascopaints)