



DURACOAT FUNGICIDAL EMULSION – SILK DDE 6

Product Description: this is a high quality silky finish emulsion paint, designed specially for areas that have high algae mould and fungal atmospheres as often found in coastal regions. It gives a good durable and washable silky sheen finish on surfaces, and is suitable for use in kitchens, bathrooms hospitals etc. which have been appropriately prepared and undercoated. This product is basically for internal use.

Finish: An even high sheen (silky) finish equal to 50% of good quality gloss enamel paint.

Application: By brush, roller, conventional or airless spray

Thinning: Supplied ready for use, therefore no thinning is required. If applied by spray, thin with water to sprayable viscosity.

Drying Time: Surface dry: 10-15 minutes. Recoating: 3 hours

Cleaning: Clean all equipment with water

Colour Range: Available in a wide range of colours from Duracoat Colour Card and Duracoat Classic Fandek.

Spread Rate: 13-15 sq.m/litre when applied on smooth plaster. Spread rate will vary if applied on rough surfaces.

Pack sizes: 1 litre, 4 litre, 20 litres

SPECIFICATIONS

New Unpainted Cement or Plaster: Apply three coats of Duracoat Fungicidal Emulsion Silk unthinned for better results. If preferred, one coat of Duracoat Vinyl Matt emulsion can be applied as first coat followed by two coats of Duracoat Fungicidal Emulsion-Silk.

Previously painted surfaces: Clean the surface and remove loose, flaking and powdery materials. Apply one coat of Duracoat Penetrating Primer followed by two coats of Duracoat Fungicidal Emulsion Silk.

Previously painted gloss surfaces: Ensure that the gloss paint is completely rubbed down to provide a key. Apply one coat of Duracoat Universal Undercoat of the desired shade followed by two coats of Duracoat Fungicidal Emulsion Silk.

Please note:

When overcoating a dark shade with a light shade, apply one coat of Duracoat Vinyl Matt Emulsion followed by two coats of Duracoat Fungicidal Emulsion Silk.