



## **DURACOAT MATT FINISH DDG 5**

**Product Description:** Duracoat Matt Finish is designed for use on wood, school board, metal or concrete surfaces where a matt finish is required. It is based on oil modified synthetic resin and good quality pigments. It provides a good grip for chalk when used on school boards.

**Finish:** Matt

**Application:** By brush, roller or spray

**Thinning:** Supplied ready for use but for ease of application thin with Duracoat White Spirit.

**Drying time:** Surface dry: 3- 4 hours. Recoating: 16 hours

**Cleaning:** Clean all equipment with Duracoat White Spirit

**Colour Range:** Black and Green or as ordered.

**Spread Rate:** The approximate spread rate is 12-14 sq mt per litre, depending on the surface texture and porosity.

**Pack Sizes:** 1 litre, 4 litres, 20 litres

### **SPECIFICATIONS:**

**New unpainted concrete surfaces:** All surfaces must be clean and dry. The first coat may be eased for brushing or rolling with up to 10 % of Duracoat White Spirit. Follow up with one or two coats of unthinned paint. Where one coat is recommended avoid thinning altogether.

**Metal surfaces:** Apply one coat of Duracoat Matt Red Oxide Primer followed by two coats of Duracoat Matt Finish

**New wood surfaces:** Apply one coat of Duracoat White Wood Primer followed by two coats of Duracoat Matt Finish

**Previously painted surfaces:** Remove all loose and flaking paint. Apply two coats of Duracoat Matt Finish.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: [customerservice@bascopaints.com](mailto:customerservice@bascopaints.com)

Facebook: BascoProductsKenya

[www.bascopaints.com](http://www.bascopaints.com)

Twitter: @bascopaints