



DURACOAT POLYURETHANE WOOD STAIN DDW 2

Product Description: Duracoat Polyurethane Wood Stain is a one pack polyurethane finish primarily intended for internal use. It is also suitable as a priming coat prior to overcoating with Duracoat Polyurethane Wood Seal Clear. Duracoat Polyurethane Wood Stain is suitable for wood flooring work, chipboard, hardboard, woodwork furniture and all other interior timber surfaces.

Finish: Matt

Application: By brush, spray or cloth pad.

Thinning: Normally supplied ready for use. If required, use Duracoat White Spirit.

Drying Time: Dust free 2-4 hours. Recoatable 24 hours.

Cleaning: Clean equipment with Duracoat White Spirit.

Colour: Available in 6 wood shades

Spread Rate: 16-18 sq. mts. per litre depending on surface porosity.

Pack Sizes: 1 litre, 4 litres.

SPECIFICATION

Surface Preparation: Surface to be coated must be clean, dry and free from oil or wax. All traces of wax or oil should be removed by power sanding particularly if wax had been used on the surface before.

New Wood Surfaces: Sand down adequately and apply one coat of Duracoat Polyurethane Wood Stain as a priming coat. This should be well brushed or ragged into the surface. When dry apply further coats until the required gloss level is achieved. If higher gloss is desired on finish, two or three coats of Duracoat Polyurethane Wood Seal Clear can be applied.

Previously Varnished Surfaces: Remove all previous varnish, loose and flaking materials, and sandpaper wood to a smooth surface. Then apply Duracoat Polyurethane Wood Stain as for new wood surfaces above.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: customerservice@bascopaints.com

Facebook: BascoProductsKenya

www.bascopaints.com

Twitter: @bascopaints