



DURACOAT RED OXIDE PRIMER DDP 6

Product Description: Duracoat Red Oxide Primer is a metal primer offering good protection from corrosion to iron and steel surfaces in milder conditions.

Finish: Matt

Application: By brush or spray

Thinning: Thin with Duracoat White Spirit. Stir well before mixing

Drying time: Dust free 2-4 hours. Recoatable: 24 hours.

Cleaning: Clean equipment with Duracoat White Spirit

Colour Range: Red oxide

Spread Rate: 11-14 sq. mts. per litre. May vary depending on surface porosity.

Pack Sizes: 1 litre, 4 litres, 20 litres

SPECIFICATIONS:

New Iron and Steel Surfaces: Surface must be clean, dry and free from grease, rust or mild scale. Apply one coat of Duracoat Red Oxide Primer. Allow 24 hours to dry before applying Duracoat Universal Undercoat.

Previously Painted Surfaces: Remove and clean all old flaking paint from the surface and clean the surface with Duracoat White Spirit. Apply one coat of Duracoat Red Oxide Primer before applying finish coat.

Galvanised Iron & Non-Ferrous Surfaces: Not recommended

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: customerservice@bascopaints.com

Facebook: [BascoProductsKenya](https://www.facebook.com/BascoProductsKenya)

www.bascopaints.com

Twitter: [@bascopaints](https://twitter.com/bascopaints)