



DURACOAT ROAD MARKING PAINT DSI 4

Product Description: Duracoat Road Marking Paint is formulated for use on concrete and bituminous surfaces forming roads, curbs and airfield runways. It is based on a rubberised resin coupled with good quality pigments and selected fillers. It is characterized by hard wearing film properties which give good durability on normal traffic pressure.

Finish: Matt

Application: By brush or road marking machine.

Thinning: No thinning is required. However, if thick on storage, restricted thinning may be applied using Duracoat Road Marking Thinner. Stir thoroughly on opening.

Colour Range: White, Black, Yellow and Red. May be available in other colours on request.

Drying time: Surface dry: 5-10 minutes. Traffic free - 30 minutes at 25⁰ C

Cleaning: Clean all equipment with Duracoat Road Marking Thinner immediately after use.

Spread rate: At thickness of 3mm, the spreading rate is 6-8 sq. mtr. per litre depending on surface porosity.

Pack Size: 1 litre, 4 litre, 20 litre

SPECIFICATION

- Ensure surface is free of loose gravel and dusts.
- Never apply on wet surface. If after rain, allow full drying before application.
- **Bitumen Surfaces:** One coat is normally sufficient on bitumen surfaces.
- **Paving Blocks, Concrete Plaster Surfaces:** Two coats are necessary if application is on paving blocks, allowing 30 mins. between coats. The first coat has to be thinned a little more for adhesion.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: customerservice@bascopaints.com

Facebook: BascoProductsKenya

www.bascopaints.com

Twitter: @bascopaints