



Duracoat Royale All Purpose Undercoat

Product Description:

Duracoat Royale All Purpose Undercoat is formulated with a special type of extender to confer good non-absorbent surface for subsequent topcoats of gloss, eggshell and water-based sheen finishes. Improved formulation gives better adhesion, excellent opacity, stops surface leaching and staining of subsequent coats. It is suitable for interior and exterior surfaces including wood, metal, plaster, stone, and asbestos, after applying an appropriate primer.

Features/Benefits:

- Extra hiding power
- Good flow, better coverage
- Excellent adhesion
- Provides non-absorbent foundation for finish coat of gloss, eggshell and water-based sheen emulsion
- Provides maximum gloss hold-up to finish coat
- High opacity, smoother finish enhances the appearance of the topcoats

Application Methods:

For detailed information please refer to the instructions on the container.

- Can be applied by brush, roller or spray gun
- Stir well before use

Thinning:

Use Duracoat White Spirit for thinning. **DO NOT** overthin.

Spreading Rate:

Spreading rate 14-18 sq.m/litre depending on the surface porosity and texture.

Surface Preparation:

All surfaces should be clean, dry and free from oil, grease, algae, mould, dirt and other impurities. Cracks and defects should be filled with suitable crack filler. Powdery or unsound surfaces should be thoroughly rubbed down and dusted off.

Application:

Can be applied by brush, roller or spray gun. For application on plaster, apply one coat of Duracoat Royale All Purpose Undercoat followed by finish coat. For application on wooden and metal surfaces apply one coat of appropriate primer followed by one coat of Duracoat All Purpose Undercoat.

Drying:

Under normal conditions surface is normally touch-dry in 4 hours. Recoatable in 12 hours.

Shade Range:

Available in white and 15 other shades. Special shades can be made available on request.

Pack Sizes:

Available in 1 litre, 4 litres and 20 litres.

Good Working Practices:

- Read instructions carefully before painting
- Ensure good ventilation during application
- When using spray gun as an application tool, wear suitable clothing and protective equipment
- Wash hands with water and soap
- Keep unused paint cans tightly closed and away from children and pets

Hints and Tips (for best results)

- Always read instructions
- Always use good quality brush
- Try to paint in one motion
- Stir well till homogeneous
- Take a small quantity of paint, thin to brushable viscosity and apply on a small area on the prepared surface to confirm shade and finish. This will avoid redoing the whole work if the shade is not suitable to your taste.

Wise Precautions:

- Avoid contacts with skin and eyes.
- After contact with skin wash immediately with plenty of soap and water. In case of contact with eye, rinse immediately with plenty of water and seek medical advice.
- Keep out of reach of children.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: customerservice@bascopaints.com

Facebook: BascoProductsKenya

www.bascopaints.com

Twitter: @bascopaints