



## **Duracoat Royale Classic Matt Emulsion**

### **Product Description:**

Duracoat Royale Classic Matt Emulsion is a technically upgraded superior premium quality acrylic emulsion paint manufactured using the best quality emulsion, pigments and extenders to confer a long lasting and aesthetically pleasing finish to any surface it is applied on. It is ideal for use on wall, ceilings, partition boards, plasters and concrete. It's virtually odour free and environmentally friendly.

### **Features/Benefits:**

- High classic matt finish
- Easy application: excellent flow and levelling
- Higher spreading rate
- Higher obliteration
- Hides minor surface defects
- Does not retain dirt
- Excellent adhesion
- Rapid drying
- Extremely durable and long lasting
- Virtually odour free
- Vast colour range – Over 4,000 shades to choose from

### **Application Methods:**

For detailed information, please refer to the instructions on the container.

- Can be applied by brush, roller or airless spray
- Stir well before use

### **Thinning:**

Thin up to 40% by volume with water. Use clean water to thin to brushable consistency. **DO NOT** overthin as this will impair the final properties of the paint film.

### **Spreading Rate:**

Spreading rate varies according to the surface porosity and texture. Approximate spreading rates on different surfaces are given below.

<b>Surfaces</b>	<b>Approx. spreading rate in sq.m/litre</b>
Newly plastered wall	10 – 14
Previously painted wall in good condition	15 – 18
Wood float/cement	11 – 14
Concrete blocks	5 – 8
Tyrolene and textured	3 – 4

### **Surface Preparation:**

All surfaces should be clean, dry and free from oil, grease and other impurities. Cracks and defects should be filled with suitable crack filler. Powdery or unsound surfaces should be thoroughly cleaned. Then apply one coat of Duracoat Pliolite surface conditioner.

**New Surfaces:**

Ensure the surface is dry. Apply one coat of Duracoat Royale All Purpose undercoat followed by 2 coats of Duracoat Royale Classic Matt Emulsion.

**Previously Painted Surfaces:**

Remove all loose, chalky, flaking materials. Powdery materials should be removed with a wire brush. Treat all surfaces with Pliolite surface conditioner. Treat surface for mould or algae if present with Duracoat Fungicidal wash. Allow to dry. Then apply a minimum of 2 coats of Duracoat Royale Classic Matt Emulsion.

**Application:**

Can be applied by brush, roller or airless spray. **Do Not** overthin.

**Drying:**

Touch-dry in 30 minutes, recoatable within 4-5 hours under normal drying conditions.

**Shade Range:**

Available from BS 4800, Duracoat Classic and Colour Plus fan decks. Special shades can be provided on request.

**Pack Sizes:**

Available in 1 litre, 4 litres, and 20 litres.

**Good Working Practices:**

- Read instructions carefully before painting.
- Ensure good ventilation during paint application.
- When using spray gun as an application tool, wear suitable clothing and protective equipment.
- Wash hands with water and soap.
- Keep unused paint cans tightly closed and away from children and pets.

**Hints and Tips (for best results)**

- Always read instructions.
- Always use good quality brush.
- Try to paint in one motion.
- Take a small quantity of paint, thin to brushable viscosity and apply on a small area on the prepared surface to confirm shade and finish. This will avoid redoing the whole work if the shade is not suitable to your taste.

**Wise Precautions:**

- Ensure good ventilation during application and drying.
- Avoid contacts with skin and eyes.
- After contact with skin wash immediately with plenty of soap and water. In case of contact with eye, rinse immediately with plenty of water and seek medical advice.
- Keep out of reach of children.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: [customerservice@bascopaints.com](mailto:customerservice@bascopaints.com)

Facebook: BascoProductsKenya

[www.bascopaints.com](http://www.bascopaints.com)

Twitter: @bascopaints