



Duracoat Royale High Build Supergloss Enamel

Duracoat Royale High Build Supergloss Enamel is an exceptionally tough, low drip enamel which imparts a luxurious finish to all interior and exterior surfaces. It's comprised of a non-yellowing, high-solids alkyd which confers excellent protection, high gloss and colour retention to painted surfaces. It is ideal for walls, ceilings, cupboards and hard wearing areas like bathrooms and kitchens as well as doors, window frames and general trim work.

Features/Benefit:

- Superior obliteration
- Long lasting
- High solids, higher film thickness
- Brilliant reflective finish
- Better flow, spreads smoothly and easily resulting in higher spreading rate
- Excellent protection and gloss
- Light-fast pigments for superior colour retention
- Low-drip, sag-resistant, no mess while painting
- Contains polyurethane for tough and hard-wearing durable film
- Easily washable
- Stain resistant
- Flexible film resists cracks and chipping
- Vast colour range – over 4,000 shades to choose from

Application Methods:

For detailed information please refer to the instructions on the container.

- Can be applied by brush, roller or airless spray
- Stir well before use

Thinning:

Use Duracoat White Spirit for thinning and cleaning equipment. **DO NOT** overthin as this can impair the flow and levelling and final gloss level of the film.

Spreading Rate:

Approximately 16-18 sq.m/litre depending on the surface porosity, texture and preparation.

Surface Preparation:

All surfaces should be clean, dry and free from oil, grease and other impurities. Cracks and defects should be filled with appropriate crack filler.

New Surfaces:

Must be primed with one coat of appropriate primer followed by 2 coats of Duracoat Royale High Build Supergloss Enamel.

Previously Painted Surfaces: Remove all loose, chalky, flaking materials. Powdery materials should be removed with a wire brush. Apply one coat of appropriate primer followed by 2 coats of Duracoat Royale High Build Supergloss Enamel.

Application:

Can be applied by brush, roller or airless spray. Thin to brushable viscosity with Duracoat White Spirit. **DO NOT** overthin.

Drying:

Touch-dry in 3-4 hours, overcoatable in 16 hours under normal drying conditions.

Shade Range:

Available from BS 4800, Duracoat Classic and Colour Plus fan decks. Special shades can be provided on request.

Pack Sizes:

Available in 1 litre, 4 litres and 20 litres.

Good Working Practices:

- Read instructions carefully before painting.
- Ensure good ventilation during paint application.
- When using spray gun as an application tool, wear suitable clothing and protective equipment.
- Wash hands with water and soap.
- Keep unused paint cans tightly closed and away from children and pets. Store in a cool dry place. Close tins tightly after use to avoid solvent loss and skinning.

Hints and Tips (for best results)

- Always read instructions.
- Always use a good quality brush.
- Try to paint in one motion.
- Take a small quantity of paint, thin to brushable viscosity and apply on a small area on the prepared surface to confirm shade and finish. This will avoid redoing the whole work if the shade is not suitable to your taste.

Wise Precautions:

- Ensure good ventilation during application and drying.
- Avoid contacts with skin and eyes.
- After contact with skin wash immediately with plenty of soap and water. In case of contact with eye, rinse immediately with plenty of water and seek medical advice.
- Keep out of reach of children.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: customerservice@bascopaints.com

Facebook: BascoProductsKenya

www.bascopaints.com

Twitter: @bascopaints