



## **Duracoat Royale Solid Matt Emulsion**

### **Product Description:**

Duracoat Royale Solid Matt Emulsion is a technically upgraded version of Superfast Emulsion formulated using premium quality binder, pigments and extenders to give solid matt finish with increased hiding power, coverage and superior performance than all other comparative products. It is highly economical, ideal for ceiling and new walls.

### **Features/Benefits:**

- Extra coverage and hiding.
- Easy application.
- Rapid drying.
- Solid matt finish.
- Hides surface imperfections.
- Cost effective.
- Suitable for contractors.
- Allows new plasters to breathe.
- Virtually odour free.
- Can be applied on all types of building surfaces which need economical yet optimum performance.

### **Application Methods:**

For detailed information please refer to the instructions on the container.

- Can be applied by brush, roller or airless spray.
- Stir well before use.

### **Thinning:**

Up to 40% by volume with water. Use clean water to thin to brushable consistency. **DO NOT** overthin as this will impair the final properties of the paint film.

### **Spreading Rate:**

Spreading rate varies according to the surface porosity and texture. Approximate spreading rates on different surfaces are given below.

<b>Surfaces</b>	<b>Approx. spreading rate in sq.m/litre</b>
Newly plastered wall	11 – 14
Previously painted wall in good condition	14 – 18
Cement rendered wood float plaster – New	10 – 12
Cement rendered wood float plaster – Previously painted	13 – 15
Concrete blocks – New, unprepared	5 – 7
Concrete blocks – Previously painted	7 – 9
Textured surfaces – New, unprepared	3 – 5
Textured surfaces – Previously painted	4 – 6

### **Surface Preparation:**

All surfaces should be clean, dry and free from oil, grease and other impurities. Cracks and defects should be filled with suitable crack filler. Powdery or unsound surfaces should be thoroughly cleaned. Then apply one coat of Duracoat Pliolite surface conditioner.

### **New Surfaces:**

No primer is required on sound masonry or soft board. Apply one coat of Duracoat Royale Solid Matt Emulsion as a priming coat, thin down with water in the ratio of 1:1 by volume. Hardboard or chipboard should be sealed with one coat of Duracoat Royale All Purpose Undercoat. Then apply 2 coats of Duracoat Royale Solid Matt Emulsion.

**Previously Painted Surfaces:** Remove all loose, chalky, flaking materials. Powdery materials should be removed with a wire brush. Treat all surfaces with Duracoat Pliolite surface conditioner. Treat surface for mould or algae if present with Duracoat Fungicidal wash. Allow to dry. Then apply a minimum of 2 coats of Duracoat Royale Solid Matt Emulsion.

### **Application:**

Can be applied by brush, roller or airless spray. **DO NOT** overthin.

### **Drying:**

Touch-dry in 30 minutes, overcoatable within 4-5 hours under normal drying conditions.

### **Shade Range:**

Available from BS 4800, Duracoat Classic and Colour Plus fan decks. Special shades can be provided on request.

### **Pack Sizes:**

Available in 1 litre, 4 litres, and 20 litres.

### **Good Working Practices:**

- Read instructions carefully before painting.
- Ensure good ventilation during paint application.
- When using spray gun as an application tool, wear suitable clothing and protective equipment.
- Wash hands with water and soap.
- Keep unused paint cans tightly closed and away from children and pets.

### **Hints and Tips (for best results)**

- Always read instructions.
- Always use good quality brush.
- Try to paint in one motion.
- Take a small quantity of paint, thin to brushable viscosity and apply on a small area on the prepared surface to confirm shade and finish. This will avoid redoing the whole work if the shade is not suitable to your taste.

### **Wise Precautions:**

- Ensure good ventilation during application and drying.
- Avoid contacts with skin and eyes.
- After contact with skin, wash immediately with plenty of soap and water. In case of contact with eye, rinse immediately with plenty of water and seek medical advice.
- Keep out of reach of children.

Facebook: BascoProductsKenya

Twitter: @bascopaints