



Duracoat Royale Silk Sheen Emulsion

Product Description:

Duracoat Royale Vinyl Silk Sheen Emulsion is a technically upgraded, superior premium emulsion paint with high quality resin, pigment and extenders. It is formulated to give subtle reflective finish with high scrub resistance. The product is suitable for high traffic areas which require regular cleaning, e.g. hallways, corridors, and reception area. It is suitable for a new and previously painted surface, e.g. plasters, cement, brick stone, soft/hard wood, asbestos sheets, etc.

Features/Benefits:

- Attractive subtle reflective sheen.
- Easily washable; cheap to maintain.
- Better coverage and improved opacity.
- Easy application.
- Virtually odour free, environment friendly.
- Suitable for high traffic areas like hallways, corridors, etc.
- Most suitable for schools, hotels, restaurants, hospitals, public buildings, etc.

Application Methods:

For detailed information, please refer to the instructions on the container.

- Can be applied by brush, roller or airless spray.
- Stir well before use.

Thinning:

Use clean water to thin to brushable viscosity. **DO NOT** overthin as this can impair the final finish and the sheen level.

Spreading Rate:

Spreading rate varies according to the surface porosity and texture. Approximate spreading rates on different surfaces are given below.

Surfaces	Aprox. spreading rate in sq.m/litre
Newly Plastered wall	12 – 14
Previously painted wall in good condition	13 – 17
Cement rendered wood float plaster – New	10 – 12
Cement rendered wood float plaster – Previously painted	12 – 14
Concrete blocks – New, unprepared	5 – 7
Concrete blocks – Previously painted	6 – 8
Textured surfaces – New, unprepared	2 – 4

Shade Range:

Available from BS 4800, Duracoat Classic and Colour Plus fandeck. Special shades can be provided on request.

Pack Sizes:

Available in 1 litre, 4 litres, and 20 litres.

Good Working Practices:

- Read instructions carefully before painting.
- Ensure good ventilation during paint application.
- When using spray gun as an application tool, wear suitable clothing and protective equipment.
- Wash hands with water and soap.
- Keep unused paint cans tightly closed and away from children and pets.

Hints and Tips (for best results)

- Always read instructions.
- Always use good quality brush.
- Try to paint in one motion.
- Always pre-test on a small area first.

Wise Precautions:

- Ensure good ventilation during application and drying.
- Avoid contacts with skin and eyes.
- After contact with skin, wash immediately with plenty of soap and water. In case of contact with eye, rinse immediately with plenty of water and seek medical advice.
- Keep out of reach of children.

Duracoat Royale Vinyl Silk Sheen Emulsion

Please read carefully to get optimum performance from this high quality product.

- Stir well till homogeneous
- Take a small quantity of paint, thin to brushable viscosity and apply on a small area on the prepared surface to confirm shade and finish. This will avoid redoing the whole work if the shade is not suitable to your taste

Duracoat Royale Vinyl Silk Sheen Emulsion is technically upgraded, superior premium emulsion paint with high quality resin, pigment and extenders. It is formulated to give subtle reflective finish with high scrub resistance. The product is suitable for high traffic areas which require regular cleaning e.g. hallways, corridors, reception area. It is suitable for a new and previously painted surface e.g. plasters, cement, brick stone, soft/hard wood, asbestos sheets, etc.

Surface preparation : All surfaces should be clean, dry and free from oil, grease, other impurities. Cracks and defects should be filled with appropriate crack filler.

New surfaces : Ensure the surface is dry. Apply one coat of Duracoat Royale All Purpose undercoat followed by 2 coats of Duracoat Royale Vinyl Silk Sheen Emulsion.

Previously painted surfaces : Remove all loose, chalky, flaking materials. Powdery materials should be removed with a wire brush. Treat all surfaces with Pliolite surface conditioner. Treat surface for mould or algae if present with Duracoat Fungicidal wash. Allow to dry. Then apply minimum 2 coats of Duracoat Royale Vinyl Silk Sheen Emulsion.

Application : Can be applied by brush, roller or airless spray. **Do Not** overthin.

Spreading capacity : 13 – 17 Sq.Mt/Ltr on smooth previously painted non porous surface.

Drying : Touch dry in 45 minutes, overcoatable within 4 – 5 hours under normal drying conditions.

Stir well before use, clean equipment with water.

If in doubt please contact our Technical department on 82355/954

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: customerservice@bascopaints.com

Facebook: BascoProductsKenya

www.bascopaints.com

Twitter: @bascopaints