



## **Duracoat Superfast Emulsion DDE 2**

### **Product Description:**

Duracoat Superfast Emulsion is a trade quality emulsion paint used for both interior and exterior. It is based on Acrylic/Vinyl copolymer resin with good quality pigments. It has excellent hiding power and the porous nature of the film allows new surfaces to breathe and dry easily. It contains lead free pigments making it non-toxic.

### **Finish:**

Matt

### **Application:**

By brush, roller or spray.

### **Thinning:**

Up to 40% water may be used to thin it down.

### **Drying time:**

Dust free: 10-15 min. Re-coating in 1-2 hours

**Cleaning:** Clean all equipment with water.

### **Colour Range:**

White and other colours from Duracoat Colour Card, Duracoat Classic and Colour Plus fandecks.

### **Spread Rate:**

The spread rate varies considerably depending on the texture, porosity of the surface being painted. The approximate spread rates are as follows:

<b>Type of Surface</b>	<b>New or Unpainted</b>	<b>Previously Painted</b>
Smooth plaster	12-13 sq.m/litre	14-15 sq.m/litre
Wood float plaster	9-10 sq.m/litre	11-12 sq.m/litre
Rough cast	4-6 sq.m/litre	5-7 sq.m/litre.

**Pack Sizes:** 1 litre, 4 litres, and 20 litres.

### **Specifications:**

#### **I. New Unpainted Concrete Surface:**

All surfaces must be clean and dry. The first coat may be eased for brushing or rolling with up to 10% of water. Follow up with one or two coats of unthinned paint. Where one coat is recommended, avoid thinning altogether.

**II. Previously Painted Surfaces:**

If existing paint work is in good condition, the surface should only be cleaned, sanded and two coats of Duracoat Superfast Emulsion applied.

**III. Brick and Asbestos:**

These should be sealed with one coat of Duracoat Acrylic Sealer to reduce absorption followed by two coats of Duracoat Superfast Emulsion paint.

**IV. Unpainted Hardboards or Plaster Boards:**

Apply one coat of Duracoat White or Pink Wood Primer followed by one coat of Duracoat Emulsion Undercoat, and then apply two coats of Duracoat Superfast Emulsion Paint.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: [customerservice@bascopaints.com](mailto:customerservice@bascopaints.com)

Facebook: BascoProductsKenya

[www.bascopaints.com](http://www.bascopaints.com)

Twitter: @bascopaints