



## **DURACOAT VARNISH STAIN DDW 3**

**Product Description:** A superior quality varnish stain available in gloss and matt finish, formulated for use on all types of timber. It is also recommended for use on newly sanded floors and timber ceilings.

**Finish:** Gloss or Matt

**Application:** By spray, brush or cloth rag

**Thinning:** When applying the first coat, thin with Duracoat White Spirit for ease of application and ensure good penetration. Subsequent coats can be thinned if necessary. For spray application thin to sprayable viscosity.

**Drying Time:** Touch dry 2-4 hours. Hard dry: 12 hours

**Cleaning:** Clean all equipment with Duracoat White Spirit

**Colour Range:** Clear, Mahogany, Light Oak, Mid Oak, etc.

**Spread Rate:** 14-16 sq. mts. per litre

**Pack Sizes:** 1 litre, 4 litres.

### **SPECIFICATIONS:**

This is a single pack, both stain and varnish designed for all types of timber.

**New surfaces:** Rub down the surface and clean with Duracoat White Spirit. Apply one coat of Duracoat Varnish Stain and let it dry. Lightly sand and clean the surface and apply two more coats.

**Previously varnished surfaces:** Remove all loose and flaking varnish, sand down and apply two coats of Duracoat Varnish Stain.

**Previously varnished surfaces in poor condition:** Remove all previous varnish with Duracoat Paint Remover then prepare surface as above and apply three coats of Duracoat Varnish Stain as in new surfaces above.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: [customerservice@bascopaints.com](mailto:customerservice@bascopaints.com)

Facebook: BascoProductsKenya

[www.bascopaints.com](http://www.bascopaints.com)

Twitter: @bascopaints

