



Duracoat Vinyl Silk Emulsion DDE 4

Product Description:

Duracoat Vinyl Silk Emulsion paint is designed to give a good durable sheen (silky) finish on surfaces which are washable and are suitably prepared and undercoated. It is ideal as a finish in living rooms, bedrooms, dining rooms, kitchens, hospital rooms, etc.

Finish:

An even, high sheen (silky) finish equal to 50% of good quality gloss enamel paint. Semi-gloss-semi-matt and rich.

Application:

By brush, rollers, conventional spray.

Thinning:

Supplied ready to use, therefore no thinning is required. If applied by spray, then thin with water to sprayable viscosity.

Drying time:

Surface dry: 20-30 minutes. Re-coating time: 3 hours.

Cleaning:

Clean all equipment with water.

Colour Range: Available in a wide range of colours from Duracoat Colour Card, Duracoat Classic and Colour Plus fandecks.

Spread Rate:

13-15 sq.m/litre when applied on smooth plaster. Spread rate will vary if applied on rough surfaces.

Pack Sizes: 1 litre, 4 litres, and 20 litres.

Specifications:

All surfaces to be painted must be clean, dry, free from dust, grease or any loose material.

New Unpainted Cement or Plaster Surfaces:

Apply three coats of Duracoat Vinyl Silk unthinned for better results. If preferred, one coat of Duracoat Vinyl Matt Emulsion can be applied as first coat followed by two coats of Duracoat Vinyl Silk Emulsion.

Previously Painted Surfaces:

Clean the surface and remove loose, flaking and powdery materials. Apply one coat of Duracoat Penetrating Primer followed by two coats of Duracoat Vinyl Silk Emulsion.

Previously painted gloss surfaces:

Ensure that gloss paint is completely rubbed down to provide a key. Apply one coat of Duracoat Universal Undercoat of the desired shade followed by two coats of Duracoat Vinyl Silk Emulsion.

Please note:

When overcoating a dark shade with a light shade, apply one coat of Duracoat Vinyl Matt Emulsion followed by two coats of Duracoat Vinyl Silk Emulsion.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: customerservice@bascopaints.com

Facebook: BascoProductsKenya

www.bascopaints.com

Twitter: @bascopaints