

# PATINA

WATER-BASED DECORATIVE SYNTHETIC WAX FOR INDOOR LIME-BASED MINERAL DECORATIVE FINISHES

## Series 319

### DESCRIPTION

PATINA is a water-based decorative wax to treat indoor lime-based mineral decorative finishes.

The use of PATINA allows obtaining high gloss surfaces. It is available in different colours with a slightly pearlescent look for an extra decorative touch.

It is easy to apply, quick drying, suitable for manual or mechanical polishing.

PATINA makes surfaces slightly water repellent.

### INSTRUCTIONS FOR USE

Can be applied on:

-Decorative mineral finishes

Evaluate the pearlescent effect best suited to the type of product to be decorated.

Application on particularly opaque surfaces changes their appearance.

Use a dry cloth to clean surfaces.

### TECHNICAL SPECIFICATIONS

-Type of Binder: polyethylene and paraffin wax compound in emulsion

-Volume mass UNI EN ISO 2811-1

Neutral: 1.01 ± 0.05 g/ml

Gold, Silver, Bronze: 1.02 ± 0.05g/ml

-Packaging viscosity: thixotropic paste

### PREPARING THE SURFACE

Walls:

Apply PATINA on lime-based mineral decorative finishes.

Surfaces must be compact, dry with no inconsistencies.

After applying the final decorative layer, wait at least 24 hours for thin finishes and at least 48 hours in case of marble stucco or similar finishes before decorating with PATINA.

### APPLICATION INSTRUCTIONS

- Room and surface conditions:

Ambient temperature: Min. +8 °C / Max. +35 °C

Relative humidity of the room: <75%

Surface temperature: Min. +5 °C / Max. +35 °C

Surface humidity: <10%

- Equipment: steel trowel and wool or fabric cloth

- Dilution: ready to use

- No. of coats: 1

- Application Method:

Spread a thin layer of PATINA using a cloth. In the presence of very flat surfaces, a stainless steel spatula can be used.

When the surface decorated with PATINA is dry, polish it using a clean cloth.

The surfaces can be polished manually or with the help of an orbital sander fitted with wool pad.

- Clean the tools with water immediately after use.

- Indicative coverage: Depends greatly on the type of surface to be covered. For smooth medium absorbent surfaces, coverage of 20 sqm/l is recommended

- Clean the tools with water immediately after use.

- Use a dry cloth to clean and preserve the surfaces treated with PATINA.

### TINTING

The product is available is a neutral colourless shade (0001) and in colours of silver (0070), bronze (0150) and gold (0190).

### STORAGE

Maximum temperature for storage stability: +30 °C

Minimum temperature for storage stability: +5 °C

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

### SAFETY RULES

Does not fall under EU directive 2004/42 (legislative decree 161/2006)

The product does not require hazardous labels under current legislation. Use the product according to the current health and safety standards; after use, do not throw containers into the environment, leave any residuals to dry completely and treat them as special waste. Keep out of reach of children. Use in a well-ventilated place. In case of contact with eyes, wash immediately with plenty of water. If swallowed, seek medical advice immediately and show the container or label. Do not empty residuals into drains, waterways or on land.

For more information, refer to the safety data sheet.

### SPECIFICATION ITEM

Interior water-based decorative wax for the treatment of indoor lime-based mineral decorative finishes. Allows obtaining high gloss surfaces. Apply one thin coat and then polish manually with a cloth or mechanically with an orbital sander fitted with a wool pad.

Coverage: 20 sqm/l depending on absorption of the finish.

PATINA does not add waterproofing properties to the surface but protects it slightly from water.

Supply and installation of the material € ..... per sqm.

*COLORIFICIO SAN MARCO guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.*