



Duracoat Soft Satin Emulsion

Product Description:

Duracoat Soft Satin Emulsion is a superior quality copolymer resin based emulsion paint formulated to give a soft satin finish to interior surfaces. It is extremely durable, fully washable and stain resistant paint suitable for high traffic areas where a soft satin finish is desired. It is also ideal for living rooms, children's rooms, ceilings, columns, partitions, kitchens and bathrooms.

Duracoat Soft Satin Emulsion is a premium grade paint which gives a satin finish to interior surfaces and has Easy Clean properties against stains. Duracoat's Fragrant Range brings a fresh and sweet smell that is appealing and welcoming.

Duracoat Fragrant Paint was developed to provide a pleasant fragrance and to help neutralize odours, including the natural odour of paint. Under optimum conditions this product produces a pleasant fragrance and helps combat odours.

Duracoat Soft Satin Emulsion is a superior quality copolymer resin based emulsion paint formulated to give a soft satin finish to interior surfaces. It is extremely durable, fully washable and stain resistant paint suitable for high traffic areas where a soft satin finish is desired. It is also ideal for living rooms, children's rooms, ceilings, columns, partitions, kitchens and bathrooms.

DIRECTIONS FOR USE

SURFACE PREPARATION:

Surfaces must be clean dry and free from dust. All loose flaking paint, mould and dust must be completely removed. Minor cracks and surface defects should be filled up with appropriate fillers.

NEW SURFACE:

Ensure the surface to be painted is fully cured (dry) especially in cases where plaster has just been carried out. Apply 1 coat of Duracoat Universal Undercoat, allow 24 hours to dry, followed by 2 coats of Duracoat Soft Satin Emulsion paint allowing 4 hours drying time between coats. The paint should be diluted to brushable viscosity with clean water (10% water is recommended of pack size).

PREVIOUSLY PAINTED SURFACE:

Remove all loose flaking materials using a scraper and sand down. Apply 1 coat of Duracoat Universal Undercoat, allow 24 hour to dry followed by 2 coats of Duracoat Soft Satin Emulsion

allowing 4 hours drying time between coats. The paint should be diluted to brushable viscosity with clean water (10% water is recommended of pack size). Before application, stir well. Do not over thin. When overcoating on a dark colour it is advisable to use 2 coats of undercoat paint preferably of the same shade. Duracoat Soft Satin Emulsion paint can be applied by brush, roller or airless spray.

THINNING:

Use clean water to thin to brushable viscosity. **DO NOT** over-thin as this can impair the final finish and the sheen level. Before application, stir well.

DRYING TIMES:

Surface will be dry in 30 minutes but allow 4 hours between coats.

SPREAD RATE:

Spread rate varies according to the surface porosity and texture. Approximate spread rates on different surfaces are given below.

Approx. Spread Rate in Sq.mts/ltr

Newly Plastered wall	13 – 14
Previously painted wall in good condition	14 – 18
Cement rendered Wood float plaster – New	11 – 13
Cement rendered Wood float plaster – Previously painted	13 – 15
Concrete blocks - New unprepared	6 – 8
Concrete blocks - Previously painted	7 – 9

STORAGE:

After painting, close the lid of the tin tightly and store in a cool dry place. Re-use in one month's time.

GENERAL:

It is recommended using a same colour undercoat for dark shades like violets, orange and red.

CAUTION:

- Keep out of the reach of children and pets.
- Not for human consumption.
- If swallowed, do not induce vomiting. Call a physician.
- Not recommended for use by asthma or allergy sufferers.
- May cause eye irritation. If contact with eyes occurs, flush with water for 15 minutes. If irritation persists, seek medical attention.

For further technical advice or any inquiries on this product, please contact our customer service department.

Basco Products (Kenya) Ltd
AN ISO 9001:2000 CERTIFIED COMPANY

NORTH AIRPORT ROAD, EMBAKASI, P.O. BOX 34424-00100, NAIROBI, KENYA
Call the Duracoat Helpline on 0800 221331 or email: customerservice@bascopaints.com
www.bascopeints.com FB: BascoProductsKenya T: @bascopeints