



Duracoat Vinyl Silk Emulsion

Product Description:

Duracoat Vinyl Silk Emulsion is a water based paint made from acrylic vinyl co-polymer emulsion resin and good quality, light fast pigments. It is designed to give good and durable sheen finish on substrates. Duracoat Vinyl Silk Emulsion has Easy Clean properties against stains and is therefore ideal to use in kitchens and heavy traffic areas.

DIRECTIONS FOR USE

SURFACE PREPARATION:

Surfaces must be clean dry and free from dust. All loose flaking paint, mould and dust must be completely removed. Minor cracks and surface defects should be filled up with appropriate fillers.

NEW SURFACE:

Ensure the surface to be painted is fully cured (dry) especially in cases where plaster has just been carried out. Apply 1 coat of Duracoat Universal Undercoat, allow 24 hours to dry, followed by 2 coats of Duracoat Vinyl Silk Emulsion paint allowing 4 hours drying time between coats. The paint should be diluted to brushable viscosity with clean water (10% water is recommended of pack size). Before application, stir well. Do not over thin.

PREVIOUSLY PAINTED SURFACE:

Remove all loose flaking materials using a scraper and sand down. Apply 1 coat of Duracoat Universal Undercoat, allow 24 hour to dry followed by 2 coats of Duracoat Vinyl Silk Emulsion allowing 4 hours drying time between coats. The paint should be diluted to brushable viscosity with clean water (10% water is recommended of pack size). Before application, stir well. Do not over thin. When overcoating on a dark colour it is advisable to use 2 coats of undercoat paint preferably of the same shade. Duracoat Vinyl Silk Emulsion paint can be applied using a brush or a roller.

DRYING TIMES:

Surface will be dry in 30 minutes but allow 4 hours between coats.

SPREAD RATE:

13-15 sq.m/litre when applied on smooth plaster. Coverage is considerably reduced when coating over rough textures.

STORAGE:

After painting, close the lid of the tin tightly and store in a cool dry place. Re-use in one month's time.

GENERAL: It is recommended using a same colour undercoat for dark shades like violets, orange and red.

CAUTION:

- Keep out of the reach of children and pets.
- Not for human consumption.
- If swallowed, do not induce vomiting. Call a physician.
- Not recommended for use by asthma or allergy sufferers.
- May cause eye irritation. If contact with eyes occurs, flush with water for 15 minutes. If irritation persists, seek medical attention.

For further technical advice or any inquiries on this product, please contact our customer service department.

Basco Products (Kenya) Ltd
AN ISO 9001:2000 CERTIFIED COMPANY

NORTH AIRPORT ROAD, P.O. BOX 34424-00100, NAIROBI, KENYA
Call the Duracoat Helpline on 0800 221331 or email: customerservice@bascopaints.com
www.bascopaints.com