



DURACOAT QUICK DRYING ENAMEL

Product Description: Duracoat Quick Drying Enamel provides a tough, hard drying finish. It is designed for use on industrial and domestic appliances, wheel barrows, manufactured tools etc. It is based on specially modified fast drying alkyds and good quality pigments.

Finish: Gloss

Application: By spray

Thinning: Thin to spraying viscosity with Duracoat Quick Drying Enamel thinner.

Cleaning: Clean all equipments with Duracoat Drying Enamel Thinner.

Drying time: Touch dry 10-20 minutes. Hard dry: 1 hour

Packaging: 4 litres, 20 litres

Colour Range: To order.

Spread Rate: 10-12 sq. mts. per litre

SPECIFICATIONS:

All the metal surfaces to be sprayed must be thoroughly cleaned and rendered from grease, moisture, rust and mill scale. Degrease the surface with solvent.

Wood to be painted should have been well seasoned and free from any residual moisture. For good results one coat of sanding sealer should be applied prior to painting with Duracoat Quick Drying Enamel.

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: customerservice@bascopaints.com

Facebook: [BascoProductsKenya](https://www.facebook.com/BascoProductsKenya)

www.bascopaints.com

Twitter: [@bascopaints](https://twitter.com/bascopaints)