



RONSEAL OUTDOOR VARNISH

Ronseal Outdoor Varnish is a unique, highly durable and flexible transparent coating for the decoration and protection of exterior woodwork. Its highly flexible alkyd formulation provides a long lasting finish resistant to cracking, peeling and blistering, which enhances the natural beauty of the wood but also protects from water and UV damage.

Ronseal Outdoor Varnish is available in gloss and satin.

INTRODUCTION

Ronseal Outdoor Varnish is a technically advanced finish, which provides long term protection for exterior woodwork. It is suitable for most types of exterior hard and softwoods and may be used on external doors, window frames and wood cladding. It may be applied to bare or previously varnished wood after appropriate preparation.

Ronseal Outdoor Varnish may also be used to refresh previously stained wood without darkening the effect.

Ronseal Outdoor Varnish advanced formulation provides extremely durable and flexible finish. The flexibility is maintained when exposed to weathering giving the varnish excellent resistance to cracking, peeling and blistering.

Ronseal Outdoor Varnish provides a clear rich, mellow finish which enhances the natural beauty of the wood. It may darken the colour of bare wood. Pretest prior to application to confirm suitability.

Ronseal Outdoor Varnish is available in gloss or satin finishes.

FIELDS OF APPLICATION

Ronseal Outdoor Varnish is recommended for use on most exterior woodwork, such as doors and door frames, window frames, cladding, garden furniture and most exterior smooth planned timber. It may also be used on previously varnished or wood stain after suitable preparation.

COVERAGE

Up to 16 sq. metres per litre per coat. Coverage will vary dependent upon the porosity of the substrate. Apply in accordance with the coverage guidelines or performance will be impaired.

DRYING TIME

Allow 6 hrs drying time per coat. Drying times will vary dependent upon prevailing temperature, humidity and the substrate.

CLEANING

Clean equipment with white spirit.

RONSEAL PAINT AND GRAIN

Ronseal Paint and Grain provides a cost effective and convenient method for transforming a variety of common interior substrates to achieve grain effect with minimal preparation of the substrate.

INTRODUCTION

Ronseal Paint and Grain, a new concept in finishing, is designed to transform most interior surfaces into an attractive grain effect without the need for stripping the substrates. The system is easy to use, without need for specialist skills or training. Ronseal Paint and Grain can be used to refurbish a wide variety of painted surfaces economically and effectively.

FIELDS OF APPLICATION

Ronseal Paint and Grain is suitable for use on most interior surfaces such as wood, paint, plastic, plaster, MDF chipboard and melamine. Ronseal Paint and Grain is ideal for kitchen units, bedroom furniture, bathroom fittings, cabinets and cupboard, painted radiators, occasional tables and many other items.

COVERAGE

Up to 24 sq mts. per litre per coat. Coverage varies significantly with the absorbency and type of surface being treated.

DRYING TIME

Ronseal Paint and Grain is touch dry in 30 minutes, recoat after 4 hours. Drying times may vary with temperature, relative humidity and absorbency of substrate.

CLEANING

Clean equipment with water and detergent.

RONSEAL HEAVY DUTY FLOOR VARNISH

Ronseal Heavy Duty Floor Varnish is a modified polyurethane varnish for decoration and protection of wooden floors. Its tough, polyurethane formula makes it suitable for floors subjects to heavy wear both in domestic and light medium commercial situations. Ronseal heavy duty floor varnish is part of the Ronseal floor care range.

INTRODUCTION

Ronseal Heavy Duty Floor Varnish provides a clear varnish which mellows and highlights the natural beauty of the wood. Ronseal Heavy Duty Floor Varnish is especially formulated for use on high traffic areas giving long-lasting protection against knocks, scratches and scuffing. The unique formulation provides excellent resistant to general household chemical. Ronseal Heavy Duty Floor Varnish is available in gloss or satin finishes for use in the home, shops and offices.

FIELDS OF APPLICATION

Ronseal Heavy Duty Floor Varnish is recommended for use on most interior flooring materials, such as hardwood strip, block and mosaic flooring, and softwood boarding, as well as cork, un-tempered hard board, chipboard and wood composition types.

COVERAGE

10-12 sq metres per litre. Coverage will vary depending on the porosity of the substrate. Apply in accordance with coverage guidelines or performance will be adversely affected.

DRYING TIME

Ronseal Heavy Duty Floor Varnish is tack free in 1-2 hours and recoatable in 4 hours. Under normal drying conditions Ronseal Heavy Duty Floor Varnish should be allowed to cure for a minimum of 4 hours prior to light foot traffic. A minimum of 24 hours should be allowed for treated areas liable to heavy foot traffic. Drying times may vary with temperature, relative humidity and absorbency of the substrate.

CLEANING

Clean equipment using white spirit.

RONSEAL QUICK DRYING VARNISH

Ronseal Quick Drying Varnish, available in a range of clear and coloured variants is polymer based to maximize performance and friendlier use. Ronseal Quick Drying Varnish gives a clear or coloured transparent finish that enhances the natural beauty of wood whilst providing long lasting protection to all interior woodwork. Ronseal Quick Drying Varnish provides a non-yellowing finish for woodwork.

INTRODUCTION

Ronseal Quick Drying Varnish provides a transparent finish which displays and highlights the rich, natural beauty of the wood. It is suitable for application to soft woods as well as cork, hardboard and chipboard in interior situations. Ronseal Quick Drying Clear Varnish does not yellow woodwork. Ronseal Quick Drying Coloured Varnish provides a coloured finish which modifies the natural colour of the wood.

Ronseal Quick Drying Varnish forms a tough durable seal bonding together the fibres of wood. It is resistant to knocks and scratches and will withstand most household chemicals. Quick Drying Varnish is suitable for most flooring applications.

Ronseal Quick Drying Gloss Varnish provides a medium gloss finish, whilst Ronseal Quick Drying Satin Varnish gives a sheen finish. The level of gloss or sheen is controlled mainly by the number of coats applied. Two or three applications are sufficient in most cases.

Ronseal Quick Drying Varnish is based on a unique water based polymer which does not yellow wood. The product has a low solvent content and low odour.

FIELDS OF APPLICATION

Ronseal Quick Drying Varnish may be used for interior applications to all softwood, hard wood, plywood, blackboard particles board and cork, windows, skirting, floor, architraves and paneling. While Ronseal Quick Drying Varnish can be used for the treatment of floors, Ronseal Quick Drying floor and cork varnish is specifically located for this application. Ronseal Quick Drying Varnish is not recommended for exterior use. Ronseal Quick Drying Varnish may also be used to refurbish and enhances the finishing of existing sound coatings on the above mentioned substrates.

COVERAGE

Up to 20 sq. metres per litre per coat. Coverage will vary with absorbency of substrates.

DRYING TIME

Ronseal Quick Drying Varnish is touch dry in 20 minutes. Drying time may vary according to prevailing temperatures, humidity levels and the substrates. Recoat time is 2 hours.

CLEANING

Clean equipment with water and detergent.

5 YEAR WOODSTAIN

Ronseal 5 Year Wood stain is the ultimate finish for exterior wood. It is independently guaranteed for a full five years. The superior quality finish has been specially developed to waterproof and protect exterior wood, giving ultimate protection.

- Independently guaranteed to last five years
- Resists cracking and peeling
- Rainproof in one hour
- Easy to apply – no primer required
- Brushes wash out in water
- **Satin** finish available

North Airport Road, Embakasi, Nairobi. Tel: (020) 6823555/954, 6823955

Email: customerservice@bascopaints.com

Facebook: BascoProductsKenya

www.bascopaints.com

Twitter: @bascopaints