

**Product Name: TRAVERTEX** 

Water-based Decorative finish with Crystal Effect Product Codes: 825 (1,5 mm) – 826 (3 mm)

## PRODUCT DESCRIPTION

Travertex is an acrylic emulsion based, ready to use, granule textured decorative coating.

- ✓ Available in two grain sizes; Fine(1mm) and coarse (3mm)
- ✓ Resistance to UV.
- ✓ High hiding power and allows walls to breathe
- ✓ Suitable for exterior walls, gross concrete, fiber cement board
- ✓ Alkali resistant

## **SURFACE PREAPARATION PECIFICATION**

All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint, and loose surface plaster. Defects and cracks should be repaired with Sandeco Acrylic Putty. Apply one coat Sandeco Uniprimer after proper thinning and allow the paint to dry fully

## **APPLICATION METHOD**

Stir well before use. Firstly, product should be applied to the surface. Distribute product evenly across the surface using a stainless steel or plastic trowel.

In order to avoid differences in shades of color please pay attention to use products with same batch numbers. Ensure that the air and surface temperatures are above 5°C during the application and 24 hours following the application



**Product Name: TRAVERTEX** 

Water-based Decorative finish with Crystal Effect Product Codes: 825 (1,5 mm) – 826 (3 mm)

## **TECHNICAL FEATURES & PHYSICAL CONSTANTS**

**COLOURS** Available in a range of SANDECO special color card

which can be further increased with special colors

**DENSITY**  $1,25 \pm 0,02 \text{ gr/cm}^3$ 

**VISCOSITY** 115- 125 KU **PH** 8 - 9,5

**VOLUME SOLIDS, %**  $86 \pm 2$  **GLOSS GRADE** Matt

FLASH POINT Non-flammable

THINNING Water

**DRYING TIME** Dry-to-touch, 4-6 hours / In depth,48 Hours

(recorded at 23°C)

**CONSUMPTION** Depending on porosity of surface and

environmental conditions 1,5 mm =  $2.000 - 3.000 \text{ kg/m}^2$ 

 $3.0 \text{ mm} = 3.000 - 3.500 \text{ kg/m}^2$ 

TEMPERATURE FOR APPLICATION + 5 °C - + 35 °C **APPLICATION TOOLS** Varnish Brush

SIZES & PACKAGING 25 kg

WARNING

STORAGE AND SHELF LIFE 1 year, unopened in cool frost-free conditions

Keep out of the reach of children. Avoid contact

with skin and eyes.