



BASCO AUTOGUARD FAST DRY ENAMEL

PRODUCT DESCRIPTION:

Basco Autoguard Fast Dry Enamel is a hard wearing paint used on truck bodies, heavy commercial machinery or equipment. It is based on a combination of good quality fast air drying resin and good quality light fast pigments which give the finish excellent durability. It is air drying and has excellent gloss and hardness combined with maximum flexibility. Basco Autoguard Fast Dry Enamel is designed to give high gloss finish straight from the gun and is therefore suited for use in large vehicles, including railway coaches, aircrafts and heavy machineries and equipment etc. It has an advantage of essentially being a one coat system which does not require polishing to enhance gloss.

TECHNICAL DATA

Finish: High Gloss. Gloss more than 80% @ 60°C on Gloss Metre.

Colour Range: As requested

Pack Sizes: ½ litre, 1 litre, 4 litres.

PAINT APPLICATION PROCESS

Product: Basco Autoguard Fast Dry Enamel

Thinning: Use Basco Synthetic Fast Dry Enamel Thinner or Basco Standard thinner.

Application: By spraying only, Recommended spraying viscosity is 26-28 seconds B4 Cup and at a pressure of 55-60 p.s.i

Priming: Basco Autoguard Fast Dry is best applied onto Basco Autoguard Cellulose Primer Surfacer or any Duracoat or Basco alkyd based primer. (For increased adhesion apply Duracoat Two Pack Etching Primer before Autoguard Primer surfacer)

Drying Time: Dust free 15-20 minutes

Re-coating is not normally necessary. However if any re-coating is required then it should be within 30 minutes of spraying the first coat. If re-coating after 2 hours or more, use only Basco Synthetic Fast Dry Enamel Thinner for thinning.

SURFACE PREPARATION:

All surfaces to be painted must be dry, clean, and free from rust, dirt, oil, grease or any other contaminants. It must be appropriately primed. In case of previously painted surfaces ensure that all loose or flaking materials are completely removed prior to painting.

CAUTION:

- Spray in well ventilated areas only.
- Wear eye goggles and protective clothing when spraying
- Do not use or keep near naked flame. **INFLAMMABLE.**
- Avoid skin and eye contact as material can be irritative.
- No polishing recommended after drying

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION