



BASCO AUTOGUARD SPOT PUTTY

PRODUCT DESCRIPTION:

Basco Autoguard Spot Putty is a cellulose based, plasticised paste that is designed to fill crevices and indentations that conspicuously stand out on dry Basco Autoguard Primers, cellulose or two pack acrylic.

TECHNICAL DATA

FINISH: Smooth and Matt

COLOUR: Grey

PACK SIZES: 1/2 kg, 1 kg, 4 kgs.

CLEANING: Clean equipment with Basco Standard Thinner.

PAINT APPLICATION PROCESS

Product: Basco Autoguard Spot Putty

Application: By pallet-knife or putty applicator.

Drying Time: Touch Dry: 10mins.

Hard Dry: 60 mins

SURFACE PREPARATION

- Applied onto dry Basco Autoguard primed surfaces.
- Application done in several thin coats allowing about 10mins interval
- Can be successfully sanded down to smooth after 90mins.
- May cause eye irritation. Wear goggles and protective clothing while handling and sanding Basco Autoguard Spot Putty.

PRECAUTION

- Spray in well ventilated areas only.
- Wear eye goggles and protective clothing when spraying
- Do not use or keep near naked flame. **INFLAMMABLE.**
- Avoid skin and eye contact as material can be irritative.
- No polishing recommended after drying.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
 REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION