



## BASCO VALUE PERMAGLOSS ENAMEL

### PRODUCT DESCRIPTION

Basco Permagloss Enamel is an economical solvent-based paint which gives a glossy finish. It forms a tough film that is resistant to stain and water and is a quality product which gives a durable finish at an affordable price. It can be applied on all types of wood, metal and concrete surfaces.

### TECHNICAL DATA

**Finish:** Gloss.

**SPREAD RATE:** 12-14 Sq.Mt/ltr depending on texture, porosity of the surface being painted.

**APPLICATION:** by Brush, Roller or Spray

**THINNING:** Up to 10% by volume with Basco Mineral Turpentine

**DRTING TIME: Surface Dry:** 4-6 hours **Re-Coating Time: 24 Hours**

**CLEANING:** Clean all equipment with Basco Mineral Turpentine

**COLOUR RANGE:** Available in a wide range of colors from the Duracoat Color Chart, Duracoat Classic Fan-Deck and Duracoat Color Plus Fan-Deck.

### SURFACE PREPARATION

All surfaces must be clean, dry and free from grease or rust. All loose and flaking paint or powdery materials must be removed completely. Apply one coat of recommended Basco Undercoat. When dry, apply 2 coats of Permagloss Enamel using brush, roller or spay.

### INGREDIENTS

Alkyd resin, pigments and approved additives.

**DISCLAIMER:** The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

**KEEP OUT OF REACH OF CHILDREN**  
**PROTECT FROM FREEZING**  
 REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION