



DURACOAT ACRYLIC ROOF PAINT

PRODUCT DESCRIPTION

Duracoat Acrylic Roof Paint is a durable and weather resistant roof coating ideal for tiled roofs and cement based surfaces.

BENEFITS

- Excellent durability in open weather
- Weather resistant roof coating
- Excellent adhesion
- Superior pigments ensure the colour remains fast

TECHNICAL DATA

FINISH: Low sheen

SPREAD RATE: 11-12 Sq.Mt/ltr

COLOURS AVAILABLE: Green, Blue, Red or as specified

PACK SIZES: 1litre, 4litres, 20litres

SURFACE PREPARATION

Surface should be free from any loose paint, dust and grease. Growths of fungus, algae or moss should be removed by scrapping.

Average: 9-11 Sq.Mt/ltr. Depends on type of surface.

Cement tiles and asbestos: 6-8 Sq.Mt/Ltr.

Granular cement tiles: 6-8 Sq.Mt/ltr,

Galvanized iron (primed): 10-12 Sq.Mt.ltr

Cement Tiles and Asbestos fibre: Apply 1 thin coat followed by 2 relatively heavy coats.

Galvanized Iron: Prime with Duracoat Etching Primer first, 1 coat of Duracoat Red Oxide Zinc Phosphate Primer, then complete with 2 coats of Duracoat Acrylic Roof Paint.

Previously Painted Surfaces: Ensure all loose flaking paint and dusts are removed. Apply coats of Duracoat Acrylic Roof Paint allowing 12 hours between coats.

PAINT APPLICATION PROCESS

Product: Duracoat Acrylic Roof Paint

Thinner: Ready for use/Clean Water

Ratio: Thin to preferred viscosity

Coats: 2/3 coats

Application: Brush, Roller, Spray. Apply liberally for best results

Drying Time: 30 minutes **Recoat:** 3-4 hours

COLOUR RANGE

Available in a wide range of colors from the Duracoat Color Chart, Duracoat Classic Fandec and Duracoat Color Plus Fandec.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
 REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION