



DURACOAT CEILING PAINT

PRODUCT DESCRIPTION

Duracoat Ceiling Paint is specifically formulated for ceilings. It is ultra flat, hiding common ceiling imperfections for a look that is virtually flawless. Duracoat Ceiling Paint provides ample open time to ensure minimal lapping and has minimal spatter.

FEATURES

- Solid hiding for imperfections
- Resists spattering when applied with roller
- Self-priming
- Tones down ceiling glare and provides maximum diffused light

TECHNICAL DATA

FINISH: Beautiful smooth matt finish. Actual coverage may vary due to method and condition of application, surface roughness and porosity.

SPREAD RATE: 10-12 Sq.Mt/ltr

COLOURS AVAILABLE: White

PACK SIZES: 1litre, 4litres, 20litres

WASHABILITY: Easy-to-clean

SURFACE PREPARATION

Surface should be free from any loose paint, dust and grease. Growths of fungus, algae or moss should be removed by wire brushing and water. Any surface cracks or holes should be raked out and filled with Duracoat Supafix Crackfiller.

New and unpainted surfaces: If the surface is dry and absorbent, apply 3 coats of Duracoat Ceiling Paint.

Previously Painted Surface: If the existing paintwork is in good condition, then the surface should be cleaned, rubbed down and two coats of Duracoat Ceiling Paint be applied.

PAINT APPLICATION PROCESS

Product: Duracoat Ceiling Paint

Thinner Ratio: Thin upto 20% volume with water

Coats: 2 to 3 for best results.

Application: Brush, Roller or Spray.

Drying Time: Touch dry: 20-30 minutes: **Recoat:** 3 hours

COLOUR RANGE

Available in white

COLOUR VISUALISER

Choosing the right combination of shades for your home can be difficult. It is at these times that you need professional help. Duracoat has the Colour Visualiser. Choose one colour from the visualiser, pick a wall to transform and play around to get the correct colour transformation. Visit our website: www.bascopaints.com for more of this service.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION

