



DURACOAT CERAMIC TILE GLUE

PRODUCT DESCRIPTION

Duracoat Ceramic Tile Glue is a good quality glue to bond ceramic tiles to wall and floor.

FEATURES

- Durable and Flexible
- Good adhesion to surfaces

TECHNICAL DATA

FINISH: Viscous gel

SPREAD RATE: 2-3 Sq. Mt/ltr

COLOURS AVAILABLE: White

PACK SIZES: 1 kg, 4 kgs & 20 kgs

SURFACE PREPARATION

Ensure that the surface is clean, dry and free from dust and grease before application.

Apply liberally to the wall or floor where the tile has to be fixed and allow 2 minutes to dry before fixing the tile. Place tiles in position and press firmly. Apply gentle pressure and allow overnight drying.

PAINT APPLICATION PROCESS

Product: Duracoat Ceramic Tile Glue

Application: Spatula or Trowel

Drying Time: 15 minutes

Recoat: 4 hours

Thinner: N/A

Drying Time: Touch dry: 15minutes **Recoat:** 4 hours

Thinner: N/A

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION