



DURACOAT CHLORINATED RUBBER PAINT

PRODUCT DESCRIPTION

Duracoat Chlorinated Rubber Paint is based on plasticized chlorinated rubber and high quality pigments. All ingredients used are chemically inert and are not affected by wide range of acids and alkalis.

FEATURES

- Durable and Flexible
- For use on internal steel surfaces in highly sensitive areas.eg. Cold Rooms
- Yields a flexible film
- Good adhesion to surfaces

TECHNICAL DATA

FINISH: Gloss or Matt

SPREAD RATE: 11-12 Sq.Mt/ltr

COLOURS AVAILABLE: Black, White and light colours as specified on our Fandeck

PACK SIZES: 1 litre, 4 litres 20 litres

SURFACE PREPARATION

Ensure that the surface is free from dust, oil or grease.

Heat Resistance: Approximately 100 degrees centigrade.

Wooden Surfaces: Prime with Duracoat Chlorinated Rubber Primer then apply two or three coats of Duracoat Chlorinated Rubber Paint.

Concrete, Plaster or Stone: The surfaces should be clean and dry. Apply one coat of Duracoat Chlorinated Rubber Primer followed by two coats of Duracoat Chlorinated Rubber Paint.

PAINT APPLICATION PROCESS

Product: Duracoat Chlorinated Rubber Paint

Thinner: Duracoat White Spirit

Ratio: To preferred viscosity

Application: Brush or roller

Drying Time: 5-10 minutes **Recoating time:** 4 hours

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION