



DURACOAT CLEARASIL

PRODUCT DESCRIPTION

Duracoat Clearsil is an excellent water repellent agent for many absorbent mineral substrates, such as bricks, sand lime brick, natural sand stone and mineral plasters. Duracoat Clearsil reduces the capillary absorption of the building which it has penetrated, but does not clog pores or capillaries. Therefore, there is little or no impairment of the building materials ability to "Breathe"

FEATURES

- Water-Based sealer for natural stone and mineral plasters.
- Ideal for interior and exterior walls
- Protects from wear caused by atmospheric agents
- Deeply penetrates the material while still allowing the surface to breathe
- Highly durable and effective beading effect
- Tack-free drying
- Provides good adhesion for paints
- Water-based and environmentally compatible
- Attractive natural effect: Does not alter surface appearance
- Long-lasting. Remains effective upto 10 years

TECHNICAL DATA

FINISH: Natural Finish

SPREAD RATE: 12-15 Sq.Mt/ltr when applied on a smooth non-porous surface

DRYING TIME: Surface Dry: 20-30 mins

APPLICATION: Apply using brush.

Two **"Wet on Wet"** coats required to ensure complete coverage and lasting effects.

If it starts to rain, stop treatment and cover the impregnated areas.

THINNING: Do not thin. Product is ready-to-use

CLEANING: Clean equipment with Duracoat White Spirit

SURFACE PREPARATION

Surface must be clean dry and free from dust, grease or any loose material before any application of Duracoat Clearsil.

PAINT APPLICATION PROCESS

Product: Duracoat Clearsil

Thinner: Read-to-use

Ratio: N/A

Coats: 1 or 2 coats

Application: Brush, Roller or Spray

Drying Time: 10-15 minutes **Recoat:** 4 hours

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint.

NOTE

- When over coating a dark shade with a light shade, three coats may be required.
- On dark shades, for example, bright reds, greens, oranges, an additional coat will be required as some have low opacity.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION

POST APPLICATION INSTRUCTIONS

- The best way to remove wall stains is to remove them immediately.
- To remove stains, sponge clean with a mild soap/detergent solution and wipe clean.
- For better washability ensure the paint surface is cured for 1 week.

APPLICATION

- Stir thoroughly before and during use.
- Always use a good quality brush.
- Try to paint in one motion.
- Always pretest on a small area first.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION

