



DURABOND 200 TILE ADHESIVE

PRODUCT DESCRIPTION

Durabond 200 is a cementitious, polymer modified tile adhesive. It contains highest grades of cement, fillers, polymers and chemical additives to give it unique properties.

FEATURES

- Excellent workability (open time)
- High bond strength
- High quality
- Non-toxic
- Easy-to-use at site

TECHNICAL DATA

FINISH: Powder

SPREAD RATE: 3-4 Sq.Mt/ltr

COLOURS AVAILABLE: Grey

PACK SIZES: 25 kgs

WASHABILITY: Easy-to-clean

SURFACE PREPARATION

The substrate must be cured, mechanically strong, free from loose particles, grease, oils, paint, wax and sufficiently dry. All surfaces must be as flat as possible.

Add 5-6 litres of clean water to suitable mixing container. Slowly add Durabond 200 powder to the water and mix until a homogenous lump free paste is achieved. DO NOT add extra water or other ingredients after mixing.

Apply Durabond 200 at 2-3mm thickness directly to the substrate using a notched trowel or spatula and spread the mortar evenly over the area to be tiled.

PAINT APPLICATION PROCESS

Product: Duracoat Durabond 200

Nature: Cementitious Powder

Application: Spatula or Trowel

Drying Time: 6 hours

Mixing Ratio: 5-6 litres water to 25 kgs bag

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION