



DURACOAT DURAPLAST EXTERIOR

PRODUCT DESCRIPTION

Duracoat Duraplast Exterior is a new improved formula based on advanced pure acrylic binder technology which provides a long-lasting low sheen finish with excellent resistance to dirt pick up. Duracoat Duraplast Exterior is specially formulated to withstand extreme tropical conditions of high rainfall, humidity and heat.

Duracoat Duraplast is formulated for use around coastal regions and areas subject to severe tropical weather conditions.

FEATURES

- Long-lasting
- Excellent UV resistance
- Beautiful low sheen
- Antialgal and Antifungal properties

RECOMMENDED FOR:

Exterior residential and commercial applications where a smooth low sheen finish with the highest performance characteristics are desired.

TECHNICAL DATA

Finish: Low Sheen

Spread Rate: 13-14 Sq.Mt/ltr when applied on Non-Porous smooth surfaces.

10-11 Sq. Mt/ltr when applied on cement rendered surfaces. Coverage is considerably reduced when coating rough textured surfaces.

PAINT APPLICATION PROCESS.

Application: Brush, roller or conventional spray.

Thinning: Use clean water up to 25% (Vol) on the 1st coat and upto 15% - 20% on subsequent coats. Do not overthin.

Cleaning: Clean all equipment with water.

Volatile Organic Compounds: < 30 gms/ltr*

Drying Time: Surface Dry: 20-30mins **Recoating time:** 3-4hrs.

Pack Sizes: 1 litre, 4 litres, 20 litres.

COLOUR RANGE

Available in a wide range of colors from the Duracoat color chart, Duracoat classic fandec and Duracoat color plus fandec.

SPECIAL COLOURS

Special colors can be made available on request

SURFACE PREPARATION:

All surfaces to be painted must be clean, dry and free from dust, grease or any loose material. For a smooth uniform finish, use Duracoat Internal and External Skim Coat for skimming.

New Unpainted Cement Or Plaster Surfaces: No priming is required when coating new or unpainted plaster, cement rendering, fair faced concrete, brick stone etc. The surface to be painted must be clean, dry and free from grease and other impurities. 3 coats are recommended allowing 4 hours between coats. If the wall is highly alkaline (pH above 9.5) then apply the first coat with Duracoat Alkali Resistant Primer followed by 2- 3 coats of Duracoat Duraplast Exterior.

Previously Painted Surface:

If the existing paint work is in good condition, then the surface should be cleaned, rubbed down and apply 2-3 coats of Duracoat Duraplast Exterior applied.

Brick and Asbestos Surfaces:

These should be sealed with one coat of Duracoat Acrylic Sealer to reduce absorption followed by 2-3 coats of Duracoat Duraplast Exterior.

COLOUR RANGE:

Available in a wide range of colors from the Duracoat Color Chart, Duracoat Classic Fandec and Duracoat Color Plus Fandec.

SPECIAL COLORS:

Special colors can be made available on request.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

APPLICATION

- Stir thoroughly before and during use.
- Always use a good quality brush.

- Try to paint in one motion.
- Always pretest on a small area first.

NOTE

- When over coating a dark shade with a light shade, three coats may be required.
- On dark shades, for example, bright reds, greens, oranges, an additional coat will be required as some have low opacity.

POST APPLICATION INSTRUCTIONS

- The best way to remove wall stains is to remove them immediately
- To remove stains, sponge clean with a mild soap/detergent solution and wipe clean.
- For better washability ensure the paint surface is cured for 1 week.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION

