



DURACOAT EGGSHELL FINISH

PRODUCT DESCRIPTION

Duracoat Eggshell Enamel is a semi-gloss oil-based finish for use on walls, wooden surfaces and high traffic areas. It is made from high quality, oil modified alkyd resins and selected light fast pigments. It gives a beautiful eggshell finish.

RECOMMENDED FOR

Wood, metal and plaster surfaces ideal for high traffic areas e.g corridors, reception areas etc.

LIMITATIONS

Do not apply when the temperature is below 10°C.

FEATURES

- Durable eggshell finish
- Withstands repeating washing
- Excellent adhesion
- For interior use
- Excellent resistance to wear and tear

TECHNICAL DATA

FINISH: Egg shell / Semigloss

SPREAD RATE: 12-15 Sq.Mt/ltr when applied on a smooth, non-porous surface.

DRYING TIME: Surface dry: 4 hours **Recoating time:** 16 hours

APPLICATION: By Brush, Roller Or Spray

THINNING: Supplied ready for use but may be thinned up to 10% with Duracoat White Spirit for ease of brushing. Avoid over thinning. Stir well before use.

CLEANING: Clean equipment with Duracoat White Spirit.

SURFACE PREPARATION

All surfaces to be painted must be clean, dry and free from dust, grease or any loose material. For a smooth uniform, use Duracoat Smotex lite or Duracoat Internal and External Skim Coat for Skimming.

New Wood Surfaces: Apply one coat of Duracoat Pink or Wood Primer or Aluminium Wood Primer followed by one coat of Duracoat Universal Undercoat. When fully dry. Apply two coats of Duracoat Eggshell Finish allowing 16 hours of drying time in between coats

Previously Painted Surfaces: Rub clean all loose flaking and powdery material from existing surface. Rub down using sand paper to provide a key finish. Apply two coats of Duracoat Eggshell finish. Allowing 16hours of drying time in between coats.

Metal Surfaces: Apply one coat of Duracoat Matt Primer Red Oxide or Duracoat Zinc Phosphate Primer followed by one coat of Duracoat Universal Undercoat. Follow on with two coats of Duracoat Eggshell finish allowing 16hours of drying time between coats. Also see technical data primers for specific metals. Non-ferrous surfaces must be primed with Duracoat Etching Primer before applying an anti-corrosive primer.

Plaster and Cement Surfaces: The surface to be painted must be dry and make sure there is no moisture on the surface. Apply one coat of Duracoat Universal Undercoat before applying two coats of Duracoat Egg shell finish allowing 16hours of drying time between coats.

PAINT APPLICATION PROCESS

Product: Duracoat Eggshell Finish

Thinner: Duracoat White Spirit

Ratio: 1 litre Duracoat White Spirit to 4 litres Eggshell Finish

Coats: 2 coats

Application: Brush, Roller or Spray.

Drying Time: Touch dry: 2-4 hours: **Recoat:** 16 hours

COLOUR RANGE

Available in a wide range of colors from the Duracoat Color Chart, Duracoat Classic Fandec and Duracoat Color Plus Fandec.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
 REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION

COLOUR VISUALISER

Choosing the right combination of shades for your home can be difficult. It is at these times that you need professional help. Duracoat has the Colour Visualiser. Choose one colour from the visualiser, pick a wall to transform and play around to get the correct colour transformation.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

APPLICATION

- Stir thoroughly before and during use.
- Always use a good quality brush.
- Try to paint in one motion.
- Always pretest on a small area first.

NOTE

- When over coating a dark shade with a light shade, three coats may be required.
- On dark shades, for example, bright reds, greens, oranges, an additional coat will be required as some have low opacity.

POST APPLICATION INSTRUCTIONS

- The best way to remove wall stains is to remove them immediately.
- To remove stains, sponge clean with a mild soap/detergent solution and wipe clean.
- For better washability ensure the paint surface is cured for 1 week.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION