



DURACOAT ETCHING SOLUTION

PRODUCT DESCRIPTION

Duracoat Etching Solution is used on blast cleaned structural steel work. It provides protection against corrosion during the fabrication period. It gives maximum adhesion on galvanised surface and all smooth ferrous and non-ferrous surfaces.

FEATURES

Easy smooth application

RECOMMENDED FOR

Interior and exterior spaces.

TECHNICAL DATA

FINISH: Clear solution

SPREAD RATE: 14-16 Sq.Mt/ltr

PACK SIZES: 1 litre & 5 litres

SURFACE PREPARATION

All surfaces must be clean, dry and free from grease, rust or mild scale.

The purpose adhesion of this solution is to chemically etch the new surfaces to enhance proper adhesion of overcoats of paint: Finishing coats. Surfaces already exposed to natural weather conditions for more than 9 months need not be treated, this will greatly improve the adhesion for consequent coats. In some cases, you can apply one coat of Etching Solution, this will greatly improve the adhesion for consequent coats.

Environmental Health & Safety Information: Duracoat Etching Solution is highly corrosive. It is recommended to wear protective clothing such as hand gloves and eye goggles when using this product.

All Surfaces: Apply 2 coats of Duracoat Etching Primer liberally on the surface using a brush. Allow to remain on the surface for at least 20 minutes. Wash off excess Etching Solution using clean water. Allow the surface to dry up completely before painting.

PAINT APPLICATION PROCESS

Product: Duracoat Etching Solution

Thinner: Ready for use

Ratio: None

Application: Brush

Activating Time: 10-20 mins

Recoat: After cleaning and drying coat with preferred primer immediately

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
 REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION