



DURACOAT FLOOR PAINT

PRODUCT DESCRIPTION

Duracoat Floor Paint is designed for use on internal concrete or cement floors. It is a coating suitable for domestic floors and light traffic shaded walkways.

FEATURES

- Hard wearing oil based coating
- Easy, smooth application
- Excellent adhesion

TECHNICAL DATA

FINISH: Semi-gloss

SPREAD RATE: 14-15 Sq.Mt/ltr

COLOURS AVAILABLE: Red oxide, Green, Grey, blue or as ordered.

PACK SIZES: 1litre, 4litres, 20litres

SURFACE PREPARATION

Surface should be free from any loose paint, dust and grease. Growths of fungus, algae or moss should be removed by scrapping.

New cement floor: Apply one coat of etching solution primer with clean water. Leave to dry then apply 2 coats of Duracoat Floor Paint.

Previously Painted Surface: Remove all loose flaking paint apply two coats of Duracoat Roof Paint allowing 16 hours drying time between coats.

PAINT APPLICATION PROCESS

Product: Duracoat Floor Paint

Thinner: Duracoat White Spirit

Ratio: Thin to preferred viscosity

Coats: 2 coats

Application: Brush

Drying Time: 3-4 hours **Recoat:** 24 hours

COLOUR RANGE

Available in a wide range of colors from the Duracoat Color Chart, Duracoat Classic Fandec and Duracoat Color Plus Fandec.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advice.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
 REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION