



## DURACOAT POLYURETHANE WOOD VARNISH STAIN

### PRODUCTION DESCRIPTION

Duracoat Polyurethane Wood Varnish Stain is a one pack Polyurethane finish. It is also suitable as a priming coat prior to overcoating with Duracoat Polyurethane Wood Seal Clear.

### FEATURES

- Preserves and enhances wood grain.
- Excellent adhesion
- Good penetration
- Easy-to-apply

### TECHNICAL DATA

**FINISH:** Matt

**SPREAD RATE:** 16-18 Sq.,Mt/ltr

**COLOURS AVAILABLE:** Clear, Mahogany, Light Oak, Mid Oak, Dark Oak, Walnut

**PACK SIZES:** 1 litre & 4 litres

### SURFACE PREPARATION

Surface should be free from any loose particles, dust and grease. Growths of fungus, algae or moss should be removed by wire brushing. Wipe with Duracoat White Spirit. Any surface cracks or holes should be raked out and filled with appropriate wood filler.

**New Wood Surface:** Apply one coat of Duracoat Polyurethane Wood Varnish Stain as a priming coat. This staining coat should be well brushed or ragged into the surface. When dry, apply two or three coats of Duracoat Polyurethane Wood Seal Gloss until the required gloss level is achieved.

**Previously Varnished Surfaces:** Remove all previous varnish, loose and flaking materials and sandpaper wood to a smooth surface. Then apply Duracoat Polyurethane Wood Seal as for new Wood Surfaces above.

**Special note:** All traces of wax or oil should be removed by power sanding particularly if wax had been used on the surface before.

### PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advice.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint.

**DISCLAIMER:** The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

**KEEP OUT OF REACH OF CHILDREN**  
**PROTECT FROM FREEZING**  
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION