



## DURACOAT QUICK AIR DRYING (Q.A.D)

### PRODUCT DESCRIPTION

Duracoat Quick Air Drying paints are coatings which produce a tough durable finish when applied to suitably prepared substrates. Drying primarily occurs from the evaporation of the carrier solvent, which is followed by a cross linking of the internal structure of the paint system.

### FEATURES

- Easy smooth application
- Outstanding durability
- Can be used on Interior or Exterior surfaces

### TECHNICAL DATA

**FINISH:** Matt

**SPREAD RATE:** 12-14Sq.Mt/ltr

**COLOURS AVAILABLE:** White, Black and a wide range of colours

**PACK SIZES:** 1 litres, 4 litres, 20 litres

### SURFACE PREPARATION

**New Ferrous Surfaces:** All metal surfaces to be sprayed or dipped must be thoroughly cleaned and rendered free from grease, moisture, rust and mild scale. Degrease the surface with a strong cleaning solvent i.e. Basco Standard Thinner or Duracoat Quick Air Drying Thinner.

**Wooden Surfaces:** If wooden surface has to be painted, it should have been well seasoned and free from any residual moisture. For good results either apply one coat of Basco Sanding Sealer or Basco Autoguard Cellulose Primer prior to painting with Duracoat Quick Air Drying Enamel.

**Galvanized surfaces:** Apply 1 coat of Duracoat Etching solution liberally on the surface using a brush. Allow to remain on the surface for at least 20 minutes. Wash off excess Etching Solution using clean water. Allow the surface to dry up completely before painting or apply 1 coat of Duracoat Etching Primer using a brush or spary. Allow it to dry for 30mins before coating with the appropriate primer followed by top coat.

### PAINT APPLICATION PROCESS

**Product:** Duracoat Quick Air Drying Enamel

**Thinner:** Duracoat Quick Air Drying Thinner

**Ratio:** Thin to preferred viscosity

**Application:** Spray, Dipping or Brush

**Drying Time: Touch dry:** 20 minutes **Recoat:** 4 hours

### COLOUR RANGE:

Available in a wide range of colors from the Duracoat Color Chart, Duracoat Classic Fandec and Duracoat Color Plus Fandec.

### COLOUR VISUALISER

Choosing the right combination of shades for your home can be difficult. It is at these times that you need professional help.

Duarcaot has the Colour visualizer. Choose one colour from the visualiser, pick a wall to transform and play around to get the correct colour transformation. Visit our website: [www.bascopaints.com](http://www.bascopaints.com) for more of this service.

### PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

**DISCLAIMER:** The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

**KEEP OUT OF REACH OF CHILDREN**  
**PROTECT FROM FREEZING**  
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION