



## DURACOAT REAL ROC

### PRODUCT DESCRIPTION

Real Roc range of textured finishes are formulated by using Light fast pigments. A special type of acrylic resin, tough aggregates, unique additives to resist fungus, algae and mould growth. It protects the exterior surfaces from rain, sun, dust.

### FEATURES

- Withstands extreme climatic conditions
- Forms a full bodied flexible film which moves with temperature and bridges hair cracks
- Contains special additives which prevent algal and fungal growth hence has excellent anti-algal/Angti fungal properties
- Thicker coating than any normal finish
- Gives extra protection because it has higher film thickness
- Has high water repellency and excellent opacity
- Is Crack resistant
- Has Excellent Heat, Light and alkali resistance
- Extremely durable and gives a beautiful matt finish

### RECOMMENDED FOR

Interior and Exterior application. It can be applied on a variety of surfaces such as plaster, brickwork, concrete, hardboard etc. by using a suitable priming coat.

We strongly recommend that only trained painters on Real Roc application are contracted to apply Real Roc textured finishes as certain specialty skills are required to achieve the desired finish and life from this product.

### TECHNICAL DATA

**FINISH:** 1.0.5mm Textured Finish.

2.1mm Textured Finish.

3.2mm Textured Finish

4.3mm Textured Finish

5.Stone Finish(Natural, 15 Colors available in this finish)

**SPREAD RATE:** Stone Finish : Approximately 4 kg for 1 sqm.

- 0.5 mm textured finish: Approximately 1.8 kg for 1 sqm.
- 1 mm textured finish: Approximately 2 kg for 1 sqm.
- 2 mm textured finish: Approximately 2.5 kg for 1 sqm.
- 3mm textured finish: Approximately 3.0kg for 1sqm.

### PAINT APPLICATION PROCESS.

**APPLICATION:** Stainless steel, trowel, plastic trowel

**THINNING:** The product is ready to use, however if thinning is required add small amount of clean water.

**DRYING TIME: Surface Dry:** 1hour **Hard Dry:** 24hours

**VOLATILE ORGANIC COMPOUNDS (VOC):** < 30gms/ltr

### COLOUR RANGE

Real Roc Range of Textured Finishes are available in over 7000 shades at Duracoat Colour Mania Centers Countrywide in 0.5mm,1mm, 2mm and 3mm finishes. Colours available in White as well as a large variety of shades in the Duracoat Color Card, Duracot Classic Fandec and Duracoat Color Plus Fandec.

Stone Finish Shades: As the stones are naturally mined we have 15 different colors in pure form which can be mixed to provide large of colors as per the customer's needs.

### PACK SIZES

5Kgs & 30kgs

### SPECIAL COLORS

Special colors can be made available on request.

**DISCLAIMER:** The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

**KEEP OUT OF REACH OF CHILDREN**  
**PROTECT FROM FREEZING**  
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION



## SURFACE PREPARATION:

All surfaces to be painted must be clean, dry and free from dust, grease or any loose material.

**New unpainted concrete Surface:** All surfaces must be clean, dry and free from dusts, grease or any loose materials. Followed up with apply one coat of Duracoat Emulsion Undercoat.

**Previously Painted Surfaces:** If existing paint work is in good condition, the surface should only be cleaned, sanded and one coat of Duracoat Emulsion Undercoat be applied.

**Brick and Asbestos Surfaces:** These should be sealed with one coat of Duracoat Acrylic Sealer to reduce absorption followed by one coat of Duracoat Emulsion Undercoat.

**Unpainted Hardboards or Plaster Boards:** Apply one coat of Duracoat White or Pink Wood Primer followed by one coat of Duracoat Emulsion Undercoat.

## APPLICATION

It is strongly recommended that one coat of a suitable undercoat be applied with a brush on all surfaces. The color of the undercoat should be close to the color of the Real Roc finishing coat. All Real Roc products should be applied with a stainless steel trowel, for finishing use a special plastic trowel. Do not apply any of the textured finish when it is raining or if the rain forecast is within 5 hours from the time you start your application.

## PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

**DISCLAIMER:** The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

**KEEP OUT OF REACH OF CHILDREN**  
**PROTECT FROM FREEZING**  
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION