



DURACOAT ROADMARKING PAINT

PRODUCT DESCRIPTION

Duracoat Road Marking Paint is formulated for use on concrete and bituminous surfaces forming roads, curbs and airfield runways. It is based on a rubberized resin.

FEATURES

- Good quality pigments and selected fillers
- Hard wearing film properties
- Good durability

TECHNICAL DATA

FINISH: Semi-gloss

SPREAD RATE: 3-4 Sq. Mt/ltr

COLOURS AVAILABLE: Yellow, Black, Red or White

PACK SIZES: 1 litre, 4 litres, 20 litres

SURFACES PREPARATION

Ensure surface is free of loose gravel and dusts. Never apply on wet surface. If application is after the rain, allow full drying before application.

Supplied ready for use. However, if thick on storage, restricted thinning may be applied using Duracoat Road Marking Thinner. Stir thoroughly on opening. Clean all equipment with Duracoat Road marking thinner.

Bitumen Surfaces: One coat of Duracoat Road marking Paint is normally sufficient on bitumen surfaces.

Paving Blocks, Concrete Plaster Surfaces: Two coats of Duracoat Roadmarking Paint are necessary. Allow 30 minutes between coats. The first coat has to be thinned a little more for adhesion and as it acts as the Priming coat.

PAINT APPLICATION PROCESS

Product: Duracoat Roadmarking Paint

Thinner: Duracoat Roadmarking Thinner

Ratio: Thin to preferred viscosity

Coats: 2 coats

Application: Brush or Roller

Drying Time: 5-10 minutes **Recoat:** 30 minutes at 25°C

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advice.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION