



DURACOAT ROOF PAINT

PRODUCT DESCRIPTION

Duracoat Roof Paint is designed for use on iron roofing sheets as a finish coat and is manufactured using the finest light fast pigments.

FEATURES

- Excellent durability in open weather
- Easy, smooth application
- Excellent adhesion

TECHNICAL DATA

FINISH: Semi-gloss

SPREAD RATE: 14-16 Sq.Mt/ltr

COLOURS AVAILABLE: Red, Green Blue

PACK SIZES: 1 litre, 4 litres, 20 litres

SURFACE PREPARATION

Surface should be free from any loose paint, dust and grease. Growths of fungus, algae or moss should be removed by scrapping.

New (Un-weathered) Galvanized Surfaces/ G C I Sheets: Degrease and apply one coat of Duracoat Two Pack Etching Primer. After 30 minutes and within 8 hours, apply one coat of Duracoat Zinc Phosphate Primer followed by two coats of Duracoat Roof Paint allowing 16 hours drying time between coats.

Previously Painted Surface: Remove all loose flaking paint apply two coats of Duracoat Roof Paint allowing 16 hours drying time between coats.

PAINT APPLICATION PROCESS

Product: Duracoat Roof Paint

Thinner: Ready for use/Duracoat White Spirit

Ratio: Thin to preferred viscosity

Coats: 2 coats

Application: Brush, Spray. Apply liberally for best results

Drying Time: 3-4 hours **Recoat:** 16 hours

COLOUR RANGE

Available in a wide range of colors from the Duracoat Color Chart, Duracoat Classic Fandec and Duracoat Color Plus Fandec.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
 REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION