



## DURACOAT SEMI-TRANSPARENT WOOD STAIN

### PRODUCT DESCRIPTION

Duracoat Semi-Transparent Wood Stain is the new generation 100% acrylic water-based exterior durable coating for wooden window or door frames. The pure acrylic resin with its own unique qualities gives outstanding beauty and protection to windows, doors and other exterior woodwork.

### FEATURES

- Resists blistering and flaking
- Contains UV filters to prevent color fade
- Highly durable finish
- Offers protection to the wood
- Excellent adhesion to properly prepared wooden substrates

### TECHNICAL DATA

**FINISH:** Gloss, Matt

**SPREAD RATE:** 13-15 Sq.Mt/Ltr

**COLOURS AVAILABLE:** Clear and other shades

**PACK SIZES:** 1 litre, 4 litres, 20 litres

### SURFACE PREPARATION

Surface should be free from any loose particles, dust and grease. Growths of fungus, algae or moss should be removed by wire brushing and water. Wipe with Duracoat white spirit. Any surface cracks or holes should be raked out and filled with appropriate crack filler.

All traces of wax or oil should be removed by power sanding particularly if wax had been used on the surface before.

**New Surfaces:** Sand the wooden substrate well, remove all dust. Apply one coat of Duracoat Semi-Transparent Wood Stain and let it dry. Lightly sand and clean the surface and apply two more generous coats.

**Previously Varnished Surfaces:** If the previously varnished area is sound (no sign of flaking, peeling, cracking) then sand well, remove all dust. Apply one coat of Duracoat Semi-transparent Wood Stain and let it dry. Lightly sand and clean the surface and apply two more generous coats.

**Previously Varnished Surfaces in Poor Conditions:** Remove all previous varnish back to bare wood, then sand well, remove all dust.

Apply one coat of Duracoat Semi-Transparent Wood Stain and let it dry. Lightly sand and clean the surface and apply two more generous coats.

### PAINT APPLICATION PROCESS

**Product:** Duracoat Semi-transparent Wood Stain

**Thinner:** Ready-to-use/ Clean Water

**Ratio:** To sprayable viscosity

**Coats:** 2 or 3 coats

**Application:** Brush or spray

**Drying Time:** 2-4 hours **Recoat:** 6 hours

**When applying by spray, thin to sprayable viscosity using clean water.**

### PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advice.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint

**DISCLAIMER:** The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

**KEEP OUT OF REACH OF CHILDREN**  
**PROTECT FROM FREEZING**  
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION