



## DURACOAT SILVER ALUMINIUM (LEAFING) PAINT

### PRODUCT DESCRIPTION

Duracoat Silver Aluminium Paint is a metallic premium quality paint designed for use internally and externally on iron and steel surfaces. Duracoat Silver Aluminium Paint has excellent heat reflecting properties and will help maintain cool temperatures of water within storage tanks. It is based on a high quality synthetic resin and leafing aluminium paste.

### FEATURES

- Excellent heat reflecting properties
- For use on internal and external Iron and Steel surfaces

### TECHNICAL DATA

**FINISH:** Bright Metallic Silver

**SPREAD RATE:** 14-16 Sq.Mt/ltr

**COLOURS AVAILABLE:** Silver

**PACK SIZES:** 1 litre, 4 litres, 20 litres

### SURFACE PREPARATION

Ensure that the surface is free from dust, oil or grease. Failure to do this will result in poor adhesion.

**New Surfaces:** Ensure all the surfaces are primed with the appropriate primer. Apply one coat to the prepared surface. Normally, one coat is sufficient but for maximum durability two coats are recommended.

**Previously Painted Surfaces:** Surface should be clean and free from loose and flaking materials.

### PAINT APPLICATION PROCESS

**Product:** Duracoat Silver (leafing) Paint

**Thinner:** Duracoat White Spirit

**Ration:** Ready to use but can be thinned to preferred viscosity.

**Coats:** 1 or 2 coats

**Application:** Brush, Roller or Spray

**Drying Time:** 1-2 hours **Recoat:** 12 hours

### PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

**DISCLAIMER:** The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

**KEEP OUT OF REACH OF CHILDREN**  
**PROTECT FROM FREEZING**  
 REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION