



DURACOAT SMOTEX (FOR ULTIMATE MULTI-USE)

PRODUCT DESCRIPTION

Duracoat Smotex is a ready mixed surfacing compound for cement plaster surfaces, appropriately primed wooden surfaces and ceiling boards, hardwood and softwood.

FEATURES

- Hide constructional imperfections
- Non-toxic
- Environmental friendly
- Doesn't crack or peel off
- Good film-breathing property
- Excellent adhesion
- Water resistant
- Excellent smoothness and superior whiteness

TECHNICAL DATA

FINISH: Rich lustrous matt

SPREAD RATE 1kg-3 kgs Sq.Mt/ltr depending on surface

COLOURS AVAILABLE: White

PACK SIZES: 1kg, 5 kgs, 20 kgs

SURFACE PREPARATION

Surface should be free from any loose paint, dust and grease. Growths of fungus, algae or moss should be removed by wire brushing and water. If the final coat is one of the high quality Duracoat Emulsions, it will be necessary to thoroughly dust off sanding residue before applying the emulsion finish. If the final coat is one of the high quality Duracoat Gloss, then one coat of Duracoat Universal Undercoat will be mandatory after thoroughly dusting off the sanded Duracoat Smotex Ultimate Smooth Finish.

New and old Cement Plaster Surfaces: Prime first, apply one coat of Duracoat Smotex Ultimate Smooth Finish on all joints and about 200MM on each side of joint. Allow to dry hard and smoothen with sand paper. If joint is too wide on plaster boards, fix with fibreglass scrim. Apply two coats of Duracoat Smotex Ultimate Smooth Finish, levelling out to smooth surface or desired hard pattern on final coat ready for decoration allowing hard drying in between coats.

Block-boards, Ceiling boards, Hard and Softwood Surfaces:

Surfaces must be well primed with Duracoat Wood Primer, Duracoat Vinylmatt or Duracoat Superfast Emulsion to satisfy the high absorbence.

Brick and Asbestos Surfaces: Same procedure as in Cement Plaster Surfaces.

PAINT APPLICATION PROCESS

Product: Duracoat Smotex Ultimate Finish

Thinner: Ready to use

Ratio: N/A

Coats: 2 coats

Application: Spatula or Trowel

Drying Time: Touch dry: 40minutes **Recoat:** 8-10 hours

COLOUR RANGE

Available in a wide range of colors from the Duracoat Color Chart, Duracoat Classic Fandec and Duracoat Color Plus Fandec.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION