



## DURACOAT SUPERFAST EMULSION

### PRODUCT DESCRIPTION

Duracoat Superfast Emulsion is a trade quality emulsion paint used for interior walls and ceilings. It has excellent hiding power and the porous nature of the film allows new surfaces to breathe and dry out easily. It contains lead free pigments making it non-toxic.

### FEATURES

- Non-Toxic
- Excellent hiding power
- Outstanding durability
- Allows the surface to breathe easily
- Excellent flow and levelling
- Better coverage

### RECOMMENDED FOR

Interior walls, ceilings, warehouses, low cost housing.

### TECHNICAL DATA

**FINISH:** Matt

**SPREAD RATE:** 12-14 Sq.Mt/ltr when applied on a smooth, non-porous surface.

**DRYING TIME: Surface Dry:** 20-30mins **Recoating Time:** 3 hours

**APPLICATION:** By Brush, Rollers Or Conventional Spray.

**THINNING:** Up to 20% (Vol.) with water if applied by brush or roller. If applied by spray, more water may be needed to adjust, more water may be needed to adjust to sprayable viscosity.

**CLEANING:** Clean all equipment with water spray equipment should be given a final rinse with Duracoat.

**VOLATILE ORGANIC COMPOUNDS (VOC):** <30gms/ltr

### SURFACE PREPARATION

All surfaces to be painted must be clean, dry and free from dust or any loose material. Cracks and defects should be filled with appropriate crack filler followed by appropriate primer. For a smooth uniform finish, use Duracoat Smotex Lite or Duracoat Internal and External Skim Coat for Skimming.

**New Unpainted Cement or Plaster Surfaces:** Apply 2-3 coats of Duracoat Superfast Emulsion.

**Unpainted Hardboards or Plaster Boards:** Apply one of Duracoat White or Pink Wood Primer followed by 2-3 coats of Duracoat Superfast Emulsion.

**Previously Painted Surfaces:** If the existing paint work is in good condition, the surface should be sanded, cleaned, made dust free and 2-3 coats of Duracoat Superfast Emulsion applied.

### COLOUR RANGE:

Available in a wide range of colors from the Duracoat Color Chart, Duracoat Classic Fandec and Duracoat Color Plus Fandec.

### PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advice.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

### APPLICATION

- Stir thoroughly before and during use.
- Always use a good quality brush.
- Try to paint in one motion.
- Always pretest on a small area first.

**DISCLAIMER:** The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

**KEEP OUT OF REACH OF CHILDREN**  
**PROTECT FROM FREEZING**  
 REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION



## NOTE

- When over coating a dark shade with a light shade, three coats may be required.
- On dark shades, for example, bright reds, greens, oranges, an additional coat will be required as some have low opacity.

## POST APPLICATION INSTRUCTIONS

- The best way to remove wall stains is to remove them immediately.
- To remove stains, sponge clean with a mild soap/detergent solution and wipe clean.
- For better washability ensure the paint surface is cured for 1 week.

**DISCLAIMER:** The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

**KEEP OUT OF REACH OF CHILDREN**  
**PROTECT FROM FREEZING**  
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION

